


PRODUCT SPECIFICATION



PRODUCT NUMBER: 1233A4T
DESCRIPTION: 12 Boat/MTW/1015

DIAMETER: 0.148
TOLERANCE +/-: 0.003

GAUGE: 12 AWG
CONDUCTORS: 1
STRANDING: 65/30 TC LHL
INSULATION: PVC
VOLTAGE: 600V DC/1000V DC
TEMPERATURE: 105 C
STYLE: Boat/MTW/1011/1015/1230/1335/1032/TEW
PRINT LEGEND: E517536 12 AWG (3.31mm2) (UL) BC-5W2 or MTW or THHW or AWM 1011/1015/1230/1335 105C 600V or 1032 1000V MOISTURE RESISTANT VW-1 -- 301259 CSA TEW or AWM I A/B 105C 600V FT1



NOM WALL: 0.030
MINIMUM WALL: 0.027

NOTES: 1. Insulating material tested to rate -40C

Tolerances unless otherwise noted: FRACTIONS +/- 1/32, DECIMALS +/- 0.03 (2PL) +/-0.005 (3PL)

Confidential: This drawing and its information are the exclusive and confidential property of Sequel Wire and Cable, LLC and are not to be disclosed, duplicated, distributed, or otherwise used without the written consent of Sequel Wire and Cable, LLC. All rights reserved.

Date	Revision	ECN	Description
09/24/2024	3		Update OD MIN TEMP