

TE Wire & Cable

The most trusted name in thermocouple wire since 1941

107 North Fifth Street • Saddle Brook, NJ 07663-6167 • 888-4TE-WIRE • www.tewire.com

PART NUMBER: PART DESCRIPTION:

FW11942 UP/ALPTWK-12-20F-JX SP

PREPARED BY: JR CUSTOMER APPROVAL/DATE:

CUSTOMER APPROVAL/DATE:

PART DESCRIPTION:

REV:

REV:

REV:

DIMENSIONS ARE IN INCHES. DIMENSIONS ARE NOMINAL UNLESS OTHERWISE SPECIFIED.

PRODUCT SPECIFICATION

CONDUCTOR TYPE: STANDARD TOLERANCE THERMOCOUPLE EXTENSION TYPE J PER ASTM E230

CONDUCTOR SIZE: 20 AWG, 7 STRANDS

INSULATION: EXTRUDED POLYVINYL CHLORIDE (PVC)

INSULATION COLOR: + WHITE, - RED

TWISTING: CONDUCTORS ARE TWISTED TOGETHER

PAIR NUMBERING: EACH CONDUCTOR PER TWISTED GROUP IS NUMBER PRINTED

CABLING: PAIRS ARE TWISTED TOGETHER

NUMBER OF PAIRS: 12

CHECKED BY: JD

OVERALL SHIELD: HELICALLY WRAPPED ALUMINUM/POLYESTER TAPE

OVERALL DRAIN: 20 AWG, 7 STRANDS, TIN PLATED COPPER

JACKET: EXTRUDED POLYVINYL CHLORIDE (PVC)

JACKET COLOR: BLACK

FINAL DIAMETER: 0.584

UL RATING: PLTC 300 V PER UL 13

PRINT LEGEND: TE WIRE & CABLE (UL) TYPE PLTC 105C 20 AWG 12 PAIR THCPL EXTN

TYPE JX SUN RES WWW.TEWIRE.COM

TEMPERATURE RATING: 105 °C

transactions are subject to compliance with our terms and conditions of sale or purchase, as applicable, which are available on our website https://tewire.com/terms-and-conditions/ or can be provided by calling the company at 201-845-9400 CONFIDENTIALITY NOTICE: This document and any attachments are confidential and may be protected by legal privilege or otherwise. If you have received this document in error, please do not read, copy, or distribute this document or any The information contained in this document is the proprietary property of TE Wire & Cable, LLC and may not be used or reproduced, in whole or in part, without the written authorization of TE Wire & Cable, LLC.

₹