



WWW.ZEUSINC.COM

PTFE, FEP, PFA, ETFE

Heavy Wall Tubing

EXTRUDED SIZES

Dimensions (Inches)



AWG	INSIDE DIAMETER			WALL DIMENSIONS	
	ID Minimum	ID Nominal	ID Maximum	Wall Nominal	Tolerance
24	.020	.022	.026	.016	+/- .003
*23	.024	.027	.030	.016	+/- .003
22	.025	.0285	.032	.016	+/- .003
*21	.030	.033	.036	.016	+/- .003
20	.032	.036	.040	.018	+/- .003
19	.036	.040	.044	.020	+/- .004
18	.040	.0445	.049	.020	+/- .004
17	.045	.0495	.054	.020	+/- .004
16	.051	.056	.061	.020	+/- .004
15	.057	.062	.067	.020	+/- .004
14	.064	.069	.074	.020	+/- .004
13	.072	.077	.082	.020	+/- .004
12	.081	.086	.091	.020	+/- .004
11	.091	.096	.101	.020	+/- .004
10	.102	.107	.112	.025	+/- .005
9	.114	.119	.124	.025	+/- .005
8	.129	.135	.141	.030	+/- .005
7	.144	.151	.158	.030	+/- .005
6	.162	.17	.178	.030	+/- .005
5	.182	.19	.198	.032	+/- .005

*AWG 23 & AWG 21 not covered under ASTM 3295 -Class 5.

Fractional Spec'd by ID/OD	O.D.	I.D.	Nominal Wall Thickness
5/32*	0.250+/- .005	0.156+/- .005	0.047

* This product is specified as HW and dimensionally manufactured to ID/OD