

Specification

US North Central 5001 S. Towne Drive New Berlin, WI 53151 800-344-2323 www.IEWC.com

Issue Date:

9/26/2013

Issue:

Construction

2 Cond GXL 18(19) PVC Jacket OAFS and Drain	Diam. (In)
2 Conductors	
18 19/.0092" (0,75mm2) to ASTM B 8-77	0.045"
0.023" XLPE to SAE J-1128 125℃	0.091"
White 2 Black	<u> </u>
2 Conductors Bunched Cabled	0.182"
Optional Fibrillated Polypropylene for roundness (our option)	0.182"
20 7/28 TC	0.182"
Aluminum Mylar Foil Shield	0.185"
0.03" PVC,Oil, Gas, Moisture and UV Resistant VW-1	0.245"
Black	0.245"
rint	
	•
SAE-J-1128 125℃ Type GXL	
	2 Conductors 18 19/.0092" (0,75mm2) to ASTM B 8-77 0.023" XLPE to SAE J-1128 125°C Color Colo

Environmental Compliance

EU Directive 2002/95/EC(RoHS):

All materials used in the manufacture of this part are in compliance with EU Directive 2002/95/EU regarding the restriction of use of certain hazardous substances in electrical and electronic equipment.

REACH Regulation (EC 1907/2006):

This product does not contain Substances of Very High Concern (SVHC) listed on the European Union's REACH candidate list in excess of 0.1% mass of the item.

California Prop 65:

The outer surface materials used in the manufacture of this part meet the requirements of California Prop. 65.

Marc Dévoulners 2013-10-24