

CPA 300

INSULATE
SEAL
PROTECT



THIN WALL ADHESIVE LINED CROSS-LINKED POLYOLEFIN

ADHESIVE LINED HEAT SHRINK TUBING IDEAL FOR APPLICATIONS WHERE BOTH EXCEPTIONAL FLAME RETARDANCY AND ENVIRONMENTAL SEALING CAPABILITIES ARE REQUIRED

FEATURES AND BENEFITS


- 3:1 shrink ratio
- Highly flame retardant
- High shrink ratio allows for coverage of irregularly shaped connectors and components
- Adhesive liner bonds to plastics, rubber, neoprene, steel and polyethylene
- Superior sealing against water, moisture and other contaminants
- Superior protection for ring terminals without excessive adhesive flow
- Continuous operating temperature: -55°C to 125°C
- Shrink temperature: 120°C

STANDARDS

- Meets SAE-AMS-DTL-23053/4, Class 3
- UL 224, 125°C
- Automotive OEM Approvals


TYPICAL APPLICATIONS

- Environmental sealing of simple in-line splices
- Strain relief and sealing of connectors and terminals
- Mechanical protection of components



DIMENSIONS

ORDER NUMBER	EXPANDED		RECOVERED						LENGTHS (STICKS)	
	INTERNAL DIAMETER (MIN.) D		INTERNAL DIAMETER (MAX.) d		TOTAL WALL THICKNESS (NOM.) W		MELTABLE WALL THICKNESS (NOM.)			
	MM	IN	MM	IN	MM	IN	MM	IN	M	IN
0125	3.2	1/8	1.0	0.040	1.0	0.040	0.5	0.020	1.2	48
0187	4.7	3/16	1.5	0.060	1.0	0.040	0.5	0.020	1.2	48
0250	6.4	1/4	2.0	0.080	1.0	0.040	0.5	0.020	1.2	48
0375	9.5	3/8	3.2	0.125	1.5	0.060	0.7	0.027	1.2	48
0500	12.7	1/2	4.1	0.160	1.8	0.070	0.8	0.030	1.2	48
0750	19.1	3/4	6.4	0.250	1.8	0.070	0.8	0.030	1.2	48
1000	25.4	1	8.1	0.320	2.5	0.100	1.0	0.040	1.2	48
1250	31.8	1¼	10.6	0.416	2.5	0.100	1.0	0.040	1.2	48
1500	39.9	1½	13.0	0.510	2.5	0.100	1.0	0.040	1.2	48



ORDERING

- Select a dimension which will shrink snugly over the component to be covered. If recovery is restricted the resultant wall thickness will be less than specified.
- Select options:
 - Colour: Black (BK), White (WT), Red (RD)
- Please specify the product name, order reference number and options you require
- Order Example: CPA 300, 0125, black, 48 in lengths

Please contact your Customer Service Representative for information on custom colours, sizes, lengths and material data sheet.

All information contained in this data sheet is believed to be reliable. We advise, however, that customers should separately evaluate the suitability of our products for their particular application. DSG-Canusa and ShawCor give no guarantees in respect of the accuracy or sufficiency of the information presented and disclaim any liability regarding its use. Our responsibilities are only those listed in our Standard Terms and Conditions of Sale for these products. In no instance will we be liable for any eventual, indirect or consequential damage or damages arising from the sale, resale, transfer, use or misuse of the product.