

SRPVC - Type 1061 (AWM)

Hook-up Wire

UL: 80°C, 300V, VW-1

CSA: 80°C, 300V, AWM I A/B, FT1



IEWC Part Number	AWG	Stranding	Nominal Insulation Thickness		Nominal O.D.		Approx. Weight	
			in	mm	in	mm	lbs/1k ft	kg/km
1061/30	30	Solid	0.010	0.3	0.030	0.8	1	1
		7/38	0.010	0.3	0.032	0.8	1	1
1061/28	28	Solid	0.010	0.3	0.033	0.8	1	1
		7/36	0.010	0.3	0.035	0.9	1	2
1061/26	26	Solid	0.010	0.3	0.036	0.9	1	2
		7/34	0.010	0.3	0.039	1.0	1	2
1061/24	24	Solid	0.010	0.3	0.041	1.0	2	3
		7/32	0.010	0.3	0.044	1.1	2	3
1061/22	22	Solid	0.010	0.3	0.046	1.2	3	5
		7/30	0.010	0.3	0.051	1.3	3	5
		Solid	0.010	0.3	0.052	1.3	4	6
1061/20	20	7/28	0.010	0.3	0.057	1.4	4	6
		10/30	0.010	0.3	0.058	1.5	4	6
		Solid	0.010	0.3	0.061	1.5	6	9
1061/18	18	16/30	0.010	0.3	0.068	1.7	6	9
		19/30	0.010	0.3	0.066	1.7	7	10
		Solid	0.010	0.3	0.071	1.8	9	14
1061/16	16	19/28	0.010	0.3	0.078	2.0	9	14
		26/30	0.010	0.3	0.080	2.0	9	14

Notes

- Soft-annealed, tinned copper conductor
- Semi-rigid polyvinyl chloride (PVC) insulation
- RoHS Compliant
- A variety of insulation colors available

Alternative Constructions

- Soft-annealed, bare copper conductor
- Topcoat conductor
- Overcoat conductor
- Prebond conductor

Available Certifications

UL: 10002

Applications

For use in electronic and appliance applications. Rated for continuous use up to 80°C.