
CAT.5E 350MHZ PATCH ETL VERIFIED TO



24 AWG (7X32) STRANDED UNSHIELDED TWISTED PAIR

ELECTRICAL CHARACTERISTIC (STANDARD)				CONSTRUCTION			
DC RESISTAN	CE (OHM/100m AT 20°C)	9.38	CONDUCTOR	NDUCTOR 24 AWG STRANDED BARE COPPER			
MUTUAL CAPAG	CITANCE (AT 1.0 kHz)	330pF/100m	INSULATION MATERIAL FOAM POLYETHYLENE		FOAM POLYETHYLENE		
IMPEDANCE (OHM AT 1-100 MHz)	100±15 OHM	INSULATION	O.D.	1.0 mm		
ATTENUATION (dB/100m AT 20°C)	FREQUENCY	ATTENUATION		MATERIAL	PVC 2		
	256 kHz 1.3 512 kHz 1.8 772 kHz 2.2 1.0 MHz 2.4 4.0 4.9	JACKET	O.D.	5.0 mm - 5.5 mm			
			COLOR	ORANGE, BEIGE, BLACK, BLUE, GREEN, GRAY, RED, WHITE, YELLOW			
	8.0	7.0	ME	MECHANICAL CHARACTERISTICS - OVERALL			
	10.0 16.0 20.0	7.8 9.8	OPERATING	TEMP RANG	GE: -20°C tO 80°C		
	20.0 25.0	11.1 12.5	BULK CA	ABLE WEIGH	TT 24.8 lbs/1000FT		
	31.25 62.5	14.0	CC	COLOR CODE / DAIRING			

FREQUENCY ATTENUATION 772 kHz 1.0 MHz 62.3 4.0 NEAR END 8.0 CROSSTALK 10.0 (dB/100m) 20.0 25.0 31.25 62.5		100.0	26.4
1.0 MHz 62.3 4.0 53.3 NEAR END 8.0 48.8 CROSSTALK 10.0 47.3 16.0 44.4 (dB/100m) 20.0 42.8 25.0 41.4 31.25 39.9		FREQUENCY	ATTENUATION
100 32.3	CROSSTALK	1.0 MHz 4.0 8.0 10.0 16.0 20.0 25.0 31.25 62.5	62.3 53.3 48.8 47.3 44.4 42.8 41.4 39.9 35.4

COLOR CODE/PAIRING (568A)					
4	4 PAIR				
PAIRED	WHITE/BLUE BLUE				
PAIRED	WHITE/ORANGE ORANGE				
PAIRED	WHITE/GREEN GREEN				
PAIRED	WHITE/BROWN BROWN				

ORANGE	UL624-80R
YELLOW	UL624-8YL
WHITE	UL624-8WT
RED	UL624-8RD
GRAY	UL624-8GY
GREEN	UL624-8GN
BEIGE	UL624-8BG
BLUE	UL624-8BU
BLACK	UL624-8BK
COLOR	PART NUMBER

 \underline{NOTE} : (XX) = COLOR OF JACKET

JACKET MARKING: "CAT.5E 350MHZ PATCH ETL VERIFIED TO ANSI/TIA-568-C.2 FOR

GIGABIT ETHERNET 24AWGX4P (UL) CM E153116 ROHS COMPLIANT xxxxFT

SHAXON INDUSTRIES
4950 EAST HUNTER AVE.
ANAHEIM, CA. 92807

DESCRIPTION:	CATEGORY 5e UTP CABLE, 24 AWG	STRANDED, 4 PAIR	снк:	APRVD:	REV.: G	DWG BY:	A. MEDINA
COLOR:	\wedge	THIS DRAWING IS THE EXCLUSIVE PROPERTY OF SHAXON I	NDUSTRIES INC I	TS ACCEPTANCE CONST	TUTES AN	DATE:	03/19/2013
COLOIN.	<u>/ </u>	AGREEMENT THAT SHOULD BE TREATED AS A STRICTLY CO	NFIDENTIAL DOCUM	MENT TO BE USED FOR	NO OTHER	DO N	OT SCALE
MATERIAL:	<u>/2</u> \	PURPOSE THAN TO AID IN THE ASSEMBLY OR OPERATION OF UNITS FURNISHED BY OR FOR SHAXON IND. INC. OR OTHERWISE AS EXPRESSLY AUTHORIZED IN WRITING BY SHAXON IND. INC. THAT IT IS RETURNED PART			PART NO.:	:	
DWG NO.	D.S. 2054	UPON REQUEST AND IS NOT TO BE COMMUNICATED, DISCI IN WRITING BY SHAXON INDUSTRIES INC. AutoCAD Release			' AUTHORIZED	UL6	524-8xx