



APPLIANCE WIRING MATERIAL

Subj.758

Section 3

Page 3190

Issued:1964-11-24

Revised:2012-10-24

Style 3190

Single conductor with extruded Insulation

---

<b>Rating</b>	105 deg C, 300 Vac, Horizontal flame, 80 deg C Oil.
---------------	---

---

<b>Conductor</b>	28 AWG - 2 AWG, bunch stranded.
------------------	---------------------------------

---

<b>Separator</b>	Paper, paper-foil, PET or PET-foil. Not required when tinned conductors are employed.
------------------	---

---

<b>Insulation</b>	Extruded CP. Conductor size, Minimum average thickness, Minimum thickness at any point; 28-9 AWG, 30 mils, 27 mils; 8-2 AWG, 45 mils, 40 mils
-------------------	---

---

<b>Assembly</b>	Paper, paper-foil, polyester, or polyester-foil separator over conductor. Not required when tinned conductors are employed.
-----------------	---

---

<b>Covering</b>	Optional, Lacquered braid.
-----------------	----------------------------

---

<b>Standard</b>	Appliance Wiring Material UL 758.
-----------------	-----------------------------------

---

<b>Marking</b>	General.
----------------	----------

---

<b>Use</b>	Internal Wiring of Appliances.
------------	--------------------------------

---

UL and the UL Logo are trademarks of UL LLC © 2017