PRODUCT SPECIFICATION

	DATE	REV	ECN	DESCRIPTION
ı	3/1/2005	Α	8067	SPECIFICATION CREATED

F01020-Parent Number:

Description: 1 7x119/30 BC Super Excelene Welding Cable

DIAMETER: 0.522

 $TOLERANCE \pm : 0.010$



MIN AVERAGE WALL: 0.080

MINIMUM WALL: 0.068

Stranding: 7x119/30 BC Unilay

Style: UL: Super Excelene Welding Cable

Insulation: CPE

Print Legend: E178457 (PLANT ID CODE) 1 AWG (UL) ROYAL (5 CROWNS LOGO) SUPER EXCELENE® WELDING CABLE 90C (-50C) OIL RESISTANT 600V -- MADE IN USA

Voltage: 600V

Temperature: 90C (-50C)

Notes:

The information presented here is, to the best of our knowledge, true and accurate. Since conditions of use are beyond Coleman Cable's control all product data presented is for informational purposes only and does not create a binding obligation or liability on Coleman Cable or confer any rights on any customer. The sale of product(s) is conditioned upon acceptance of a purchase order subject to Coleman Cable's standard terms and conditions contained therein, including without limitation Coleman Cable's standard warranty. Coleman cable disclaims all liability in connection with the use of information contained herein or otherwise.

This specification is proprietary intellectual property of Coleman Cable. Any information contained herein shall not be disclosed to any party without written consent of Coleman Cable.

Customer	An	pro	val:
C ttbtctc.		P	****

Title: _____Company Name: ____ Coleman Cable, Inc.

1115 W. North Street Bremen, IN 46506

Phone: 1-574-546-5115

www.colemancable.com

