



HOOK-UP WIRE

MIL-W-16878/4
SOLID CONDUCTOR
TYPE E-600V

**Description:**

Solid Silver Plated Copper, Extruded PTFE Insulation.

Characteristics:

Temperature Rating:

MIL-W-16878: -60°C to +200°C

UL 1213: +105°C

Voltage Rating:

MIL-W-16878: 600V

UL 1213: Not Rated Passes UL VW-1 Flame Test

WEICO NO.	MILITARY NO.	CONDUCTOR		NOM. WALL THICKNESS	NOM. O.D. (IN)
		SIZE	STRAND		
2830	M16878/4BBA-X	30	Solid	.010	.030
2828	M16878/4BCA-X	28	Solid	.010	.033
2826	M16878/4BDA-X	26	Solid	.010	.036
2824	M16878/4BEA-X	24	Solid	.010	.040
2822	M16878/4BFA-X	22	Solid	.010	.045
2820	M16878/4BGA-X	20	Solid	.010	.052
2818 *	M16878/4BHA-X	18	Solid	.010	.060

*Not UL listed

COLORS:

0 - Black, **1** - Brown, **2** - Red

3 - Orange, **4** - Yellow, **5** - Green

6 - Blue, **7** - Violet, **8** - Gray, **9** - White

X Denotes 0 - 9 color coding

STRIPES:

Any of the above colors are available in any combination of stripes up to a maximum of three stripes.

Standard Put-Ups: 100 ft., 1000 ft.