



ATLAS WIRE CORPORATION
9525 RIVER STREET
SCHILLER PARK, ILLINOIS 60176
(847) 678-1210
(847) 678-1281 FAX
atlaswirecorp.com



ATLAS WIRE CORPORATION
REGISTERED TO ISO 9002
CERTIFICATE NO. A4894

MATERIAL SPECIFICATION SHEET

#18 16/30 TC .017" PVC

RoHS COMPLIANT

MIL SPEC

MIL-16878/2 TYPE C 1000V-105C

MIL-W-76D TYPE MWP 1000V - 90C

CONDUCTOR: #18 16/30 TINNED COPPER 1" BUNCHED
NOMINAL O.D. .048"
APPROXIMATE CIRCULAR MILL AREA 1,600
WEIGHT PER THOUSAND FEET 5.00#
BASIC SPECIFICATION ASTM B 174

LEAD-FREE PVC:

TEMPERATURE RATING TYPE C	105c
VOLTAGE RATING	1000 VOLTS
WALL THICKNESS	.017"
FINISHED OD	.082"
ELONGATION	330% AVERAGE
TENSILE STRENGTH	2850 PSI AVERAGE
SPECIFIC GRAVITY	1.35
DUROMETER (SHORE)	92 (A)
OXYGEN INDEX	29
BRITTLE POINT	-25c
SPARK TESTED	5,000 VOLTS
WEIGHT PER THOUSAND FEET	7.08#

REVISION: M1L-W-16878E/2 - NO PRINTING REQUIRED*
M1L-W-16878G/2 - PRINT REQUIRED*

* OUR STANDARD IS UNPRINTED, IF PRINTING IS REQUIRED
PLEASE CALL THAT OUT AT TIME OF ORDER.