1. CONDU	CTOR:
----------	-------

1.1 Size and Material: 22 7/30 AWG tin-plated copper wire.

## 2. INSULATION:

- 2.1 Extruded silicone rubber.
- 2.2 Marking on the insulation: as per Nema Standard.
- 2.3 O.D.: .093" nom.
- 2.4 Color: as per order (replace X in the part number and at the end of the description by 0-9 color code).

## 3. PERFORMANCE:

- 3.1 Voltage rating: 1000 VAC R.M.S.
- 3.2 Temperature rating: 150°C

## 4. REFERENCES:

4.1 NEMA Standards Publication No. HP 6.

<b>CUS</b>	IED	<b>ADD</b>		/ A I
GUO	IER	AFF	RUI	V AL

Sign: _		 	
Date:			

	Engine	ering Ch	ange No	ice No.	

**UNCONTROLLED DOCUMENT** A later revision of this specification may exist.

This specification is the property of Harbour Industries Canada Limited and may not be used or copied without the express written permission of Harbour Industries Canada Limited.

Done:	Prive Garand			
Date:	May 29, 2014			

Verified: Tamir lote Date:

May 29, 2014 Scale:

1 of 1

Size:

1365, boul. Industriel, Farnham, Quebec, Canada, J2N 2X3 Phone: (450) 293-5304 Fax: (450) 293-2421 Web site: www.harbourind.com

Description:

Code Ident. No:

57104

**HP 6-SS-HFBX** 

Specification No.:
F04891-X
Wire & C

Rev.