



HOOK-UP WIRE



MIL-W-16878/1

TYPE B - 600V

Description:

Stranded Tinned Copper, Color Coded Polyvinylchloride Insulation

Characteristics:

Temperature Rating: -55°C to +105°C

Voltage Rating: 600V

Passes UL VW-1 Flame Test

WEICO NO.	MILITARY NO.	CONDUCTOR		NOM. WALL THICKNESS	NOM. O.D. (IN)
		SIZE	STRAND		
1130	M16878/1BBB-X	30	7/38	.010	.032
1128	M16878/1BCB-X	28	7/36	.010	.034
1126/1	M16878/1BDA-X	26	Solid	.010	.036
1126	M16878/1BDB-X	26	7/34	.010	.038
1126/19	M16878/1BDE-X	26	19/38	.010	.038
1124/1	M16878/1BEA-X	24	Solid	.010	.040
1124	M16878/1BEB-X	24	7/32	.010	.043
1124/19	M16878/1BEE-X	24	19/36	.010	.043
1122/1	M16878/1BFA-X	22	Solid	.010	.045
1122	M16878/1BFB-X	22	7/30	.010	.050
1122/19	M16878/1BFE-X	22	19/34	.010	.050
1120	M16878/1BGB-X	20	7/28	.010	.058

WEICO NO.	MILITARY NO.	CONDUCTOR		NOM. WALL THICKNESS	NOM. O.D. (IN)
		SIZE	STRAND		
1120/19	M16878/1BGE-X	20	19/32	.010	.058
1118	M16878/1BHB-X	18	7/26	.010	.068
1118/19	M16878/1BHE-X	18	19/30	.010	.068
1116/19	M16878/1BJE-X	16	19/29	.010	.077
1114/19	M16878/1BKE-X	14	19/27	.010	.091

COLORS:

0 - Black, 1 - Brown, 2 - Red
3 - Orange, 4 - Yellow, 5 - Green
6 - Blue, 7 - Violet, 8 - Gray, 9 - White
X Denotes 0 - 9 color coding

STRIPES:

Any of the above colors are available in any combination of stripes up to a maximum of three stripes.

Standard Put-Ups: 100 ft., 1000 ft.