


16/2C Type SOOW Black



PRODUCT DATA SHEET

SOOW portable cord is recommended for use as portable electrical power and portable control wire cable. With its flexibility and resistance to the effects of abrasion, chemicals, weather and ozone, it is excellent for heavy-duty cable service applications. This cable is rated to 600 volts and has a temperature range of -40°C to +90°C. These characteristics make SOOW portable cord an excellent choice for mitigating outdoor factors.



Design Number 10039
Part Number 32104492
Customer Number N/A

Color Code: Black, White

CONSTRUCTION

Conductor: Stranded bare copper, Class K per ASTM B-174
Conductor Size: 16AWG, 26 strands
Insulation: EPDM, oil resistant
Insulation Avg. Thickness: 0.030"(Nom.)
Insulated Conductor O.D.: 0.124"(Nom.)
Filler: PP
Separator: Paper
Jacket Material: CPE, oil resistant
Jacket Avg. Thickness: 0.060"(Nom.)
Overall Diameter: 0.378"(Nom.)
Jacket Color: Black

ELECTRICAL CHARACTERISTICS

Operating Temperature (°C): -40°C to +90°C
Operating Voltage: 600V
Flame Test : CSA FT2

SAFETY CHARACTERISTICS

RoHS Compliance: European Directive 2015/863/EU
Approvals: UL Flexible Cord, Subject 62
CSA Flexible Cord, C22.2 No.49
MSHA Approved

Print Legend:

ASCENT E486041 16AWG 2/C SOOW (UL) 600V (-40 -90C)--CSA LL268042
FT-2 WATER RESISTANT P-07KA140001-MSHA --RoHS xxxxxFT

Application: Industrial tools, portable lights, battery chargers and equipment that is typically exposed to oils, solvents, flame and grease, also may be used for ground tests and motor leads.

All trademarks are property of their respective owners. All specifications are subject to change.

Revision History		
00	2019/07/16	Initial release
01	2022/12/15	New part number added
Created L. Jian	Approved A. Huang	

Milwaukee | 5001 South Towne Dr. New Berlin, WI 53151, USA
Frankfurt | Rudolf-Braas-Strasse 2, D-61381 Friedrichsdorf, Germany
Luton | Unit 11, Humphrys Road, Woodside Industrial Estate, Dunstable, LU5 4TP, UK
Suzhou | B2-2 Weiting Industrial - Workshop A, No. 9 Weixin Road, Suzhou Industrial Park, China

