UL CMG/2464 22AWG/3C Gray



PRODUCT DATA SHEET

Cable is suitable for installation under NEC (NFPA 70) article 800 guidelines. Cable is suitable for installation in Canada under Section 60 of CEC, Part I. Internal wiring or external interconnection of electronic equipment.


Design Number	10384
Part Number	32130965
Customer Number	N/A

CONSTRUCTION

Conductor: Stranded tinned copper Conductor Size: 22AWG(7/30) Insulation: Polyvinyl Chloride Insulation Thickness: 0.010"(Nom.) Insulation Diameter: 0.050"(Nom.) Cable Lay Length: 2.00"(Nom.) Jacket Material: Polyvinyl Chloride Jacket Thickness: 0.030"(Nom.) Overall Diameter: 0.167"(Nom.) Jacket Color: Gray

Print Legend (Footage Markers):

ASCENT E478021 22AWG 3C 75C C(UL)US CMG SUN RES FT4 OR AWM 2464 300V 80C "ROHS COMPLIANT" MADE IN USA



Color Code: Black, White, Red

ELECTRICAL CHARACTERISTICS

Operating Temperature (°C): 80°C Operating Voltage: 300V Weight: 17 Lbs/Mft

SAFETY CHARACTERISTICS

C(UL)US listed as CMG per UL standard 444 and per CSA C22.2 No. 214-17 UL recognized component as AWM 2464, 80°C, 300V per UL standard 758 Cable meets (UL) 1685 FT4 flame test Cable meets RoHS 2002/95/EC Directive, RoHS 2 2011/65/EU Directive, RoHS 3 2015/863/EU Directive **Cable is REACH compliant per Regulation (EC) No 1907/2006 (240) Updated January 23, 2024**

Application: Internal wiring or external interconnection of electronic equipment

All trademarks are property of their respective owners. All specifications are subject to change.

Milwaukee | 5001 South Towne Dr. New Berlin, WI 53151, USA Frankfurt | Rudolf-Braas-Strasse 2, D-61381 Friedrichsdorf, Germany Luton | Unit 11, Humphrys Road, Woodside Industrial Estate, Dunstable, LUS 4TP, UK Suzhou | B2-2 Weiting Industrial - Workshop A, No. 9 Weixin Road, Suzhou Industrial Park, China



Rev	Revision History			
00	2020/09/14	nitial Release		
01	2024/06/20	The print legend is updated		
Г				
Cre	ated L. Jian	Approved A. Huang		