

Specifications

- * ASTM B33: Tinned Standard Specification for Soft or Annealed Copper Wire
- * ASTM B174: Standard Specification for Bunch-Stranded Copper


Construction

- 1) Conductor: Class K stranded tinned copper per ASTM B 33 and 174
- 2) Insulation: Heat, moisture and oil resistant EPDM. Color: Black, White, Red, Green, Orange, Blue, White/Blk, Red/Blk
- 3) Filler: Paper fillers as needed
- 4) Binder: Binder as needed
- 5) Jacket: Black Chlorinated Polyethylene CPE

Applications and Features

Southwire Non UL/Non CSA control cord is designed for use with light industrial equipment, tools, battery chargers, portable lights and power extensions.

Print Legend

Stock Code	Conductor Size (Strands)	Conductor Diam	Number of Conductors	Insulation Thickness	Jacket Thickness	Approx. Overall OD	Approx. Weight	Min Bend Radius	Ampacity 75C/90C
	AWG	inches		mils	mils	inches	Lbs./1,000'	inches	amps
645837	20 (26)	0.036	8	20	50	0.385	86	1.5	



Drawn By:	S.S.	Req By:	D.H.	11/17/2020
Ticket #:	22447	Drawing #:	SS2576	Rev: