

# 14AWG/4C OAS/BRD VNTC

(UL)TC-ER 600V C(UL) CIC TC CSA AWM WTTTC DP-1



PRODUCT DATA SHEET

Cable is suitable for installation under NEC (NFPA 70) article 336 guidelines.  
Cable is suitable for installation in Class I Division 2 hazardous locations.  
Suitable for torsional applications which are typical for the loop in wind turbine generators (WTG).


**Design Number** 10602  
**Part Number** 32164958  
**Customer Number** N/A

## CONSTRUCTION

**Conductor:** Stranded bare copper  
**Conductor Size:** 14AWG(41/0.010")  
**Insulation Material:** Polyvinyl Chloride/Nylon  
**Insulation Thickness:** 0.015"/0.005"(Nom.)  
**Insulation Diameter:** 0.112"(Nom.)  
**Shield Tape:** Aluminum/Mylar  
**Drain Wire:** Tinned copper, 18AWG 7 strand  
**Braid:** 36AWG, Tinned copper, 70% Coverage  
**Jacket Material:** TPE, pressure extruded  
**Rip Cord:** Yes (1-Ply)  
**Jacket Thickness:** 0.0475"(Nom.)  
**Overall Diameter:** 0.391"(Nom.)  
**Jacket Color:** Black

### Print Legend (Footage Markers):

TC-1404SH 14AWG/4C SHIELDED ASCENT E478019-LU (UL) TC-ER 600V PVC/NYLON  
90C DRY/WET 90C JKT SUN RES OIL RES II DIR BUR OR DP-1 OR MTW FLEXING 600V  
OR AWM 20886 1KV 90C OR C(UL) TC CIC 90C DRY 75C WET FT4 -25C OR CSA  
604274 AWM I/II A/B 90C DRY 75C WET 1KV FT1 FT2 FT4 -40C **CE** ROHS  
MADE IN USA XXXXX FT



**Color Code:** Black #1 ~#3, Green/Yellow

## ELECTRICAL CHARACTERISTICS

**Operating Temperature (°C):** 90°C  
**Operating Voltage:** UL/CSA 600V(TC-ER, MTW, CIC), WTTTC 1000V  
UL/CSA 1000V(AWM)

**Weight:** 130 Lbs/Mft

**Min. Bend Radius:** 6x OD

**Attributes:** Cable meets UL 1581 & 1202(FT-4) 70,000 BTU/HR  
Individual conductors pass UL VW-1 flame test, rated THWN-2/VW-1

## SAFETY CHARACTERISTICS

UL listed as Type TC-ER per UL Standard 1277 for Tray Cables  
UL listed as Type WTTTC per UL Standard 2277 for wind turbine tray cables  
UL listed as MTW and DP-1 per UL Standard 1063,1690  
UL recognized component as Type 20886 per UL Standard 758 for appliance wiring material  
Listed as Type CIC TC per CSA Standard C22.2 No. 239-17 & No.230-09 for Instrumentation and control cable and tray cables  
CSA listed as Type AWM per CSA Standard 22.2 No.210-11 for appliance wiring material products  
In compliance with the Low Voltage Directive 2006/95/EC  
Product is marked CE in accordance with EC Declaration of Conformity  
**RoHS Compliant:** European Directive 2015/863/EU  
**REACH:** Regulation (EC) No 1907/2006 Updated June.27, 2018

**Application:** Torsion resistant for drip loops, Industrial machinery, Compliant with tool machines, Plant engineering, Wind Turbine Tray Cable, Outdoor use and Direct burial in the USA

All trademarks are property of their respective owners. All specifications are subject to change.

Revision History		
00	2022/03/09	Initial Release
01	2022/03/25	Conductor numbers updated from 5 to 4, Print legend updated
02	2022/04/14	Print legend updated
03	2022/05/18	Print legend updated
04	2022/07/18	Print legend updated and Part Number
Created L. Jian		Approved A. Huang

**UK HQ** | Unit 11, Humphrys Road, Woodside Industrial Estate, Dunstable, LU5 4TP UK  
**Frankfurt** | Rudolf-Braas-Strasse 2, D-61381 Friedrichsdorf  
**Milwaukee** | 5001 South Towne Dr. New Berlin, WI 53151 USA  
**Suzhou** | B2-2 Weiting Town Industrial - Workshop A, No. 9 Weixin Rd., Suzhou Industrial Park, Jiangsu, China 215122

