
10/5C Type SOOW Black H07RN-F 450/750V 5G6



PRODUCT DATA SHEET

SOOW portable cord is recommended for use as portable electrical power and portable control wire cable. With its flexibility and resistance to the effects of abrasion, chemicals, weather and ozone, it is excellent for heavyduty cable service applications. This cable is rated to 600 volts and has a temperature range of - 40° C to + 90° C. These characteristics make SOOW portable cord an excellent choice for mitigating outdoor factors.



Design Number10Part Number32Customer NumberN/

10895 32187187 N/A

CONSTRUCTION

Conductor: Stranded bare copper, Class K per ASTM B-174 Conductor Size: 10AWG(86/0.30mm) Insulation: EPDM, oil resistant Insulation Thickness: 1.14mm(Nom.) Filler: Rubber strip in central Separator: Non-woven tape Jacket Material: CPE, oil resistant Jacket Thickness: 2.41mm(Nom.) Overall Diameter: Nom20.0mm, Max 20.3mm Jacket Color: Black

Print Legend: ASCENT E486041-11 10AWG(6.08mm²) 5C SOOW UL 600V (-40C-90C) ----

Color Code: Green/Yellow, Blue, Brown, Black, Grey

ELECTRICAL CHARACTERISTICS

Operating Temperature (°C): -40°C to +90°C **Operating Voltage:** 600V **Approx. Weight:** 660 kg/km

SAFETY CHARACTERISTICS

Flame Test: CSA FT2 Approvals: UL Flexible Cord, Subject 62 CSA Flexible Cord, C22.2 No.49 RoHS Compliant

Application: Industrial tools, portable lights, battery chargers and equipment that is typically exposed to oils, solvents, flame and grease, also may be used for ground tests and motor leads.

All trademarks are property of their respective owners. All specifications are subject to change.

Revision History		
00	2023/12/06	Initial release
Г		
Г		
Г		
Created L. Jian		Approved A. Huang

Milwaukee | 5001 South Towne Dr. New Berlin, WI 53151, USA Frankfurt | Rudolf-Braas-Strasse 2, D-61381 Friedrichsdorf, Germany Luton | Unit 11, Humphrys Road, Woodside Industrial Estate, Dunstable, LU5 4TP, UK Suzhou | B2-2 Weiting Industrial - Workshop A, No. 9 Weixin Road, Suzhou Industrial Park, China

