

U.I. Lapp GmbH	PRODUCT INFORMATION	
	EPIC® SIGNAL M23 Contacts female	05.11.2015

Contacts, tools, accessories for circular connectors M23



Good chemical resistance



Corrosion-resistant



Mechanical resistance



Oil-resistant



Optimum strain relief



Robust



Reliability



Info

All contacts are high quality gold plated
 Contacts are designed for wide crimping range, therefore low number of variants
 Contacts in solder or crimp version available

Remark

Photographs are not to scale and do not represent detailed images of the respective products.

Product Management	Document: LAPP_PRO136970EN.pdf	1 / 3
--------------------	--------------------------------	-------

EPIC® SIGNAL M23 Contacts female

05.11.2015

Part number	Article designation	Version	For design	Pieces / PU
1mm contacts female				
74020601	EPIC® M23 BCEMS 1 mm AU 0.14 - 1.0 (10)	1 mm female slot 0.14 - 1.0 mm ²	per inserts M23 (not D-Sub), LS1 D6, A6	10
74200600	EPIC® M23 BCEMS 1 mm AU 0.14 - 1.0 (100)	1 mm female slot 0.14 - 1.0 mm ²	per inserts M23 (not D-Sub), LS1 D6, A6	100
72402601	EPIC® M23 BLEMS 1 mm 1.0 AU (10)	1 mm female slot solder	M23 inserts (not D-Sub)	10
72402600	EPIC® M23 BLEMS 1 mm 1.0 AU (100)	1 mm female slot solder	M23 inserts (not D-Sub)	100
74034500	LS1 D BCEMS 1 mm AU 0.14 - 1.0 (100)	1 mm female hyperboloid 0.14 - 1.0 mm ²	per inserts M23 (not D-Sub), LS1 D6, A6	100
74034501	LS1 D BCEMS 1 mm AU 0.14 - 1.0 (10)	1 mm female hyperboloid 0.14 - 1.0 mm ²	per inserts M23 (not D-Sub), LS1 D6, A6	10
2mm contacts female				
72401601	EPIC® M23 BCEMS 2 mm AU 1,0 - 2,5 (10)	2 mm female crimp	M23 inserts (not D-Sub)	10
72401600	EPIC® M23 BCEMS 2 mm AU 1,0 - 2,5 (100)	2 mm female crimp	M23 inserts (not D-Sub)	100
72404100	EPIC® M23 BLEMS 2 mm AU 1,0 - 2,5 (10)	2 mm female solder	M23 inserts (not D-Sub)	10
72404000	EPIC® M23 BLEMS 2 mm AU 1,0 - 2,5 (100)	2 mm female solder	M23 inserts (not D-Sub)	100

U.I. Lapp GmbH	PRODUCT INFORMATION	 LAPP GROUP
	EPIC® SIGNAL M23 Contacts female	05.11.2015



Product Management	Document: LAPP_PRO136970EN.pdf	3 / 3
--------------------	--------------------------------	-------