18/2 Type SVO Black



PRODUCT DATA SHEET

SVO power cable is commonly used in 300 volt applications for household appliances and electronic equipment. It is best for light-duty use applications, including vacuum cleaners, office equipment, and more.


Design Number	10688
Part Number	600002549
Customer Number	N/A

CONSTRUCTION

Conductor: Stranded bare copper Conductor Size: 18AWG, 41 strands Insulation: EPDM Insulation Avg. Thickness: 0.015" (Nom.) Insulation Diameter: 0.083" (Nom.) Filler: Tear rope Jacket Material: CPE Jacket Avg. Thickness: 0.030" (Nom.) Overall Diameter: 0.236" (Nom.) Jacket Color: Black

Print Legend:

ASCENT E486041 18AWG 2/C SV0 (UL) 300V 90C --C(UL) 18AWG 2/C SV0 300V 90C FT2 RoHS



Color Code: 1. Black 2. White

ELECTRICAL CHARACTERISTICS

Operating Temperature (°C): 90°C **Operating Voltage:** 300V **Conductor Resistance @ 25°C:** 22.4 Ω/km Max **Flame Test :** CSA FT2

SAFETY CHARACTERISTICS

Approvals: UL Flexible Cords and Cables, Subject 62 C(UL) approval meets CSA standard C22.2 No.49 Flexible cords RoHS Compliant

Application: Such as food preparing machines, lamps, clocks, fans, blowers, personal computers, monitors and printers.

All trademarks are property of their respective owners. All specifications are subject to change.

Revision History		
00	2022/11/24	Initial release
Created L.Jian		Approved A. Huang

Milwaukee | 5001 South Towne Dr. New Berlin, WI 53151, USA Frankfurt | Rudolf-Braas-Strasse 2, D-61381 Friedrichsdorf, Germany Luton | Unit 11, Humphrys Road, Woodside Industrial Estate, Dunstable, LU5 4TP, UK Suzhou | B2-2 Weiting Industrial - Workshop A, No. 9 Weixin Road, Suzhou Industrial Park, China

