


# Technical Data Sheet

## CCTV + Power Coaxial Cable

**WEST PENN WIRE**



2833 West Chestnut Street  
 Washington, PA 15301  
 Toll Free: (800) 245-4964  
 Fax: (724) 222-6420  
 www.westpenn-cdt.com

<b>PART NUMBER:</b>	<b>2815B</b>
<b>DESCRIPTION:</b>	RG59/U 20AWG Bare Copper, 95% Braid + 2 Conductor 18AWG – Siamese Construction
<b>NEC RATING:</b>	CM
<b>APPROVALS:</b>	(UL) or (ETL)us Listed
<b>APPLICATION:</b>	CCTV Indoor Baseband video

### Construction Parameters: Coaxial Cable

Conductor	20 AWG Bare Copper RG59/U
Stranding	Solid
Insulation Material	Gas Injected Polyethylene (PE)
Insulation Thickness	0.138" Nom.
Shield	95 % Bare Copper Braid
Jacket Material	PVC

### Nom. Attenuation

Mhz	db/100ft
1	.29
10	.68
50	1.80
150	3.0
200	3.54
400	4.71
1000	7.80

### Electrical & Environmental Properties: Coaxial Cable

Temperature Rating	-20deg C to 60deg C
Operating Voltage	300 V RMS
Max. Capacitance Between Conductors @ 1 KHz	16.2pf/ft Nom.
Nom. Velocity of Propagation	82%

### Construction Parameters: Power Pair

Conductor	18 AWG Bare Copper
Stranding	7x26
Insulation Material	PVC
Insulation Thickness	0.010" Nom.
Number of Conductors	2
Shield	None
Drain	None
Jacket Material	PVC

### Electrical & Environmental Properties: Power Pair

Temperature Rating	-20°C To +60°C
Operating Voltage	300 V RMS
Max. Capacitance Between Conductors @ 1 KHz	30 pf/ft Nom.
DC Resistance per Conductor @ 20deg C	6.2 Ohms/1M' Nom.
Insulation Colors	Black ,Red

### Construction Parameters: Overall Cable

Jacket Material	PVC
Overall Cable Diameter	.232" x .465"
Jacket Colors	Black
Flame Rating	UL1685
RoHS Compliant	Yes

## **Mechanical Properties:**

Max. Recommended Pull Tension  
Min. Bend Radius (Install)

-- Lbs.  
4.65

### Connectors:

75ohm BNC Crimp	CN-BM74-32
Compression BNC	CN-BNC59MCV

Specification Issue Date: 4/12

This document is the property of West Penn Wire.  
The information contained herein is considered  
Proprietary and not to be reproduced by any means  
Without written consent of West Penn Wire

Standard Lengths are 1000ft.  
The Jacket is sequentially footmarked.  
The information presented here is, to the best of our  
knowledge, is true and accurate. However, since  
conditions of use are beyond our control, all  
recommendations or suggestions are presented  
without guarantee or responsibility on our part. We  
disclaim all liability in connection with the use of  
information contained herein or otherwise.