

N19-44T-447-9G
7 CONDUCTOR CABLE:

28 AWG SHIELDED ISOLATED TWISTED PAIR:
2(28 AWG 40/44 TINNED COPPER, .005" POLYPROPYLENE TO
.025" +/- .001" OD - BLACK-WHITE) CABLED WITH LS
POLYESTER FILLERS (2 FILLERS IN EACH INTERSTICE), 40
AWG TINNED COPPER SPIRAL SHIELD, 95% MIN COVERAGE,
.001" CLEAR MYLAR TAPE, 50% LAP

28 AWG SINGLES (5):
28 AWG 40/44 TINNED COPPER, .005" POLYPROPYLENE TO
.025" +/- .001" OD - BROWN, GREEN, BLUE, RED, ORANGE

CABLE 28 AWG SHIELDED ISOLATED TWISTED PAIR AND FIVE
28 AWG SINGLES AROUND AN ARAMID STRENGTH MEMBER AND LS
POLYESTER FILLERS IN THE INTERSTICES

40 AWG TINNED COPPER SPIRAL SHIELD, 95% MIN COVERAGE

.001" PAPER TAPE, 50% LAP

.0155" GRAY POLYURETHANE JACKET TO .137" +/- .003" OD

MINIMUM = 1000 FEET

FINISHED WEIGHT = (12.99#/KFT) (0.0193KG/MTR)

Spool Size: 12" PLASTIC-A

RoHS Compliant 2002/95/EC & 2011/65/EU

This product is NAFTA eligible.