



A: (2) 24 AWG 2C 7 Strands Tinned Copper Foam Polypropylene Insulated
 Wire Size & Stranding: 24 AWG 7/32
 Metal Type: Annealed Tinned Copper
 Nominal Wire Diameter: 0.024

Insulation Type: Foam Polypropylene
 Nominal Insulation Thickness: 0.023
 Nominal Conductor Diameter: 0.070
 Color Code: Blue x White

Cable Lay Length: 2.25 Left Hand Lay
 Heat Fusible Aluminum/Mylar - 100% Coverage
 24 AWG 7 Strands Tinned Copper Drain Wire
 Black Polyvinylchloride Jacket, Nominal Jacket Thickness: 0.019, Pressure Extruded

B: 12 AWG 3C 65 Strands Tinned Copper Polyvinylchloride Insulated

Wire Size & Stranding: 12 AWG 65/30
 Metal Type: Annealed Tinned Copper
 Nominal Wire Diameter: 0.093

Insulation Type: Polyvinylchloride
 Nominal Insulation Thickness: 0.031
 Nominal Conductor Diameter: 0.155
 Color Code: Black, Red, Green

C: Fibrillated Polypropylene - as needed for a circular cross-section

D: Non-Woven Polyester Wrap - 100% Coverage

E: Black Polyvinylchloride Jacket, Nominal Jacket Thickness: 0.060, Pressure Extruded

Nominal Cable Lay Length: 6.75 Left Hand Lay

Legend: TBD

Notes:
 Print Type: White Ink
 Footage Markers: N/A
 Ripcord: N/A
 Weight: 188 lbs.



12 AWG 3C PVC + (2) 24 AWG 2C PP SHIELDED PVC JKT O/A POLYVINYLCHLORIDE JACKET			
All Dimensions are Shown In Inches		PROPRIETARY DOCUMENT	
Third Angle Projection		THIS DRAWING MAY CONTAIN PATENTED OR PROPRIETARY INFORMATION AND MUST NOT BE REPRODUCED, DISTRIBUTED OR USED FOR MANUFACTURING WITHOUT THE WRITTEN CONSENT OF LAKE CABLE, LLC. ACCEPTANCE OF THIS DRAWING WILL BE CONSTRUED AS AN AGREEMENT TO AND ACCEPTANCE OF THE FOREGOING.	
Drawn By: RIR	Scale: 3 : 1	Cust. #: -	REV -
Reviewed By: -	Sheet: 1 of 1	Lake's #: 140911RIR1	REV -
Cage Code: N/A	Date Created: 09/16/14		

Revision	Description	Approved By	Date
-	-	-	-