

Description: Eight Conductor Composite Cable
 PVC Insulation and PVC Jacket

Date: 2/24/2010

JM Part Number: JM55966

Reference: M4410

Components

Component A: Two 18 AWG Insulated Conductors

Conductor: 18 AWG, 19/30 tinned copper

Insulation: .017" nominal wall of PVC .082"

Colors: Black and Red

Component B: Six 20 AWG Insulated Conductors

Conductor: 20 AWG, 19/32 tinned copper

Insulation: .017" nominal wall of PVC .073"

Colors: Green, Brown, Blue, Orange, Red/White, and Brown/White

Cable Construction

Cabling: Two A components, Six B components, fillers as necessary

Binder: Clear Mylar tape

Jacket: .037" nominal wall of Black PVC .326"

Print

E66440  AWM 2598 2/C 18 AWG 6/C 20 AWG 60C 300V TOMAR P/N M4410

Requirements

Temperature: 60C

Approvals: UL AWM Style 2598

Voltage: 300V

Written By:	rjc	2/24/2010	Rev. 0	Initial Issue
Revised By:	scs	3/4/2010	Rev. 1	Added JM and Reference Numbers, Revised Print Legend
Revised By:	scs	7/22/13	Rev. 2	Revised Tomar P/N in print legend
Revised By:				