

**Picture
Not Available**

For more Information
please call

1-800-Belden1



General Description:

Video Cable, Riser-CMR, 6-25 AWG solid tinned copper, foam polyethylene insulation, Duobond®+95% tinned copper interlocked serve, PVC jacket, 2 pairs - 22 AWG stranded tinned copper, PVC insul., Beldfoil® shield, drain wire, PVC jacket, overall PVC jacket.

Usage (Overall)

Suitable Applications:

Projection Video, Projectors, Classroom, Room-to-Room AV, RGB, VGA, SVGA, XGA, SXGA, USGA, HDTVM LCD, Plasma, Component Video, Video Mult., Composite Audio Video, Hybrid Component, Animation, Special Effects, RGB62, TGB6C/22-2P, High Resolution, HR + STP 22-175

Coax

Physical Characteristics

Conductor

AWG:

# Coax	AWG	Stranding	Conductor Material	Dia. (mm)
6	25	Solid	TC - Tinned Copper	0.457

Insulation

Insulation Material:

Insulation Material	Dia. (mm)
Gas-injected FHDPE - Foam High Density Polyethylene	1.880

Inner Shield

Inner Shield Material:

Layer #	Inner Shield Trade Name	Type	Inner Shield Material	% Coverage (%)
1	Duobond®	Tape	Aluminum Foil-Polyester Tape-Bonded Aluminum Foil	100
2		Interlocked Serve	TC - Tinned Copper	95

Inner Jacket

Inner Jacket Material:

Inner Jacket Material	Nom. Dia. (mm)
PVC - Polyvinyl Chloride	2.896

Inner Jacket Color Code Chart:

Number	Color
1	Red
2	Green
3	Blue
4	Yellow
5	Black
6	White

Mechanical Characteristics

Min. Bend Radius (Install):

27.940 mm

Electrical Characteristics

Nom. Characteristic Impedance:

Impedance (Ohm)
75

Nom. Inductance:

Inductance (µH/m)
0.285

Nom. Capacitance Conductor to Shield:

Capacitance (pF/m)
55.777

Nominal Velocity of Propagation:

VP (%)
80.000

Nominal Delay:

Delay (ns/m)
4.068

Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/km)
111.554

Nom. Inner Shield DC Resistance:

DCR @ 20°C (Ohm/km)
17.717

Minimum Return Loss:

Start Freq. (MHz)	Stop Freq. (MHz)	Min. RL (dB)
5.000	850.000	20.000

Nom. Attenuation:

Freq. (MHz)	Attenuation (dB/100m)
1.000	1.706
5.000	3.839
50.000	12.140
100.000	16.077
200.000	21.983
400.000	31.170
750.000	43.965
900.000	49.215
1000.000	51.840
3000.000	102.367

Max. Operating Voltage - UL:

300 V RMS

Twisted Pair

Physical Characteristics

Conductor

AWG:

# Pairs	AWG	Stranding	Conductor Material
2	22	7x30	TC - Tinned Copper

Insulation

Insulation Material:

Insulation Material
PVC - Polyvinyl Chloride

Twisted Pair Color Code Chart:

Number	Color
1	Black and Red
2	Black and Red

Inner Shield

Inner Shield Material:

Inner Shield Trade Name	Type	Inner Shield Material	Coverage (%)
Beldfoil®	Tape	Aluminum Foil-Polyester Tape	100

Inner Shield Drain Wire AWG:

AWG	Stranding	Conductor Material
24	Stranded	TC - Tinned Copper

Inner Jacket

Inner Jacket Material:

Inner Jacket Material	Nom. Dia. (mm)
PVC - Polyvinyl Chloride	3.581

Inner Jacket Color Code Chart:

Number	Color
1	Brown
2	Orange

Mechanical Characteristics

Min. Bend Radius (Install):

38.100 mm

Electrical Characteristics

Nom. Capacitance Conductor to Conductor:

Capacitance (pF/m)
150.926

Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/km)

52.824

Nom. Inner Shield DC Resistance:

DCR @ 20°C (Ohm/km)

37.732

Max. Operating Voltage - UL:

Voltage

300 V RMS

Max. Recommended Current:

Current

2.8 Amps per conductor @ 25°C

Physical Characteristics (Overall)

Conductor

Overall Cable

Overall Cabling Color Code Chart:

Number	Color
1	Red
2	Green
3	Blue
4	Yellow
5	Black
6	White
7	Brown
8	Orange

Overall Nominal Diameter: 11.049 mm

Mechanical Characteristics (Overall)

Operating Temperature Range: 0°C To +75°C

Separation Temperature Range: 0°C To +75°C

Bulk Cable Weight: 125.009 Kg/Km

Max. Recommended Pulling Tension: 822.917 N

Min. Bend Radius/Minor Axis: 114.300 mm

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

NEC/(UL) Specification: CMR

CEC/C(UL) Specification: CMG

EU Directive 2011/65/EU (ROHS II): Yes

EU CE Mark: Yes

EU Directive 2000/53/EC (ELV): Yes

EU Directive 2002/95/EC (RoHS): Yes

EU RoHS Compliance Date (mm/dd/yyyy): 02/13/2007

EU Directive 2002/96/EC (WEEE): Yes

EU Directive 2003/11/EC (BFR): Yes

CA Prop 65 (CJ for Wire & Cable): Yes

MII Order #39 (China RoHS): Yes

Applicable Patents:

Country

www.belden.com/p

Flame Test

UL Flame Test: UL1666 Riser

CSA Flame Test: FT4

Plenum/Non-Plenum

Plenum (Y/N): No

Plenum Number: 6788AV

Put Ups and Colors:

METRIC MEASUREMENT VERSION

5788AV Composite - Audio and Video Composite Cable

Item #	Putup	Ship Weight	Color	Notes	Item Desc
5788AV 0001000	1,000 FT	90.000 LB	NONE	C	BONDED FILLER COMPOSITE
5788AV 000250	250 FT	24.500 LB	NONE	C	BONDED FILLER COMPOSITE

Notes:

C = CRATE REEL PUT-UP.

Revision Number: 0 Revision Date: 02-28-2014

© 2015 Belden, Inc.
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein. All sales of Belden products are subject to Belden's standard terms and conditions of sale. Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product. Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.