

N23-36T-264-2UL
Customer P/N: 0014CBDSS-0NE

14 CONDUCTOR CABLE

24 AWG TWISTED PAIRS (5):
2(24 AWG 19/36 TINNED COPPER, .010" (.009" MIN) ETFE
TO .044"
+/- .002" OD - BLACK-WHITE, RED-GREEN, YELLOW-BLUE,
BROWN-ORANGE,
GRAY-VIOLET TO UL AWM 10316), CABLED

18 AWG SINGLES (4):
18 AWG 19/30 TINNED COPPER, .011" (.010" MIN) ETFE TO
.070"
+/- .002" OD - GREEN, RED, BLACK, WHITE TO UL AWM
10316

CABLE FOUR 24 AWG TWISTED PAIRS AND FOUR 18 AWG
SINGLES AROUND
(24 AWG TWISTED PAIR PLUS FIBRILLATED POLYPROPYLENE
FILLER)
PER DRAWING

.002" UNSINTERED PTFE TAPE, 50% LAP

38 AWG TINNED COPPER SPIRAL SHIELD, 90% MIN COVERAGE

38 AWG TINNED COPPER SPIRAL SHIELD, 90% MIN COVERAGE

.002" UNSINTERED PTFE TAPE, 50% LAP

.045" BLACK POLYURETHANE JACKET TO .389" +/- .012" OD
TO UL AWM
20233 80C, 30V