



QC3618

Specification Sheet

Lake Cable Part #: S182C2213CT-NUL

Description: Two element composite cable, cabled together with an overall tissue wrap & PVC jacket. Non-UL

- 18 AWG 2 Conductors 16 Strands Tinned Copper PVC
- 22 AWG 13 Conductors 7 Strands Tinned Copper PVC

Element 1: 18 AWG 2 Conductors 16 Strands Tinned Copper PVC

1. Conductor

- 1.1. AWG Size & Stranding: 18 AWG 16 Strands Class K
1.2. Material: Annealed Tinned Copper
1.3. Conductor Count: 2 Conductors

2. Insulation

- 2.1. Material: Polyvinylchloride
2.2. Wall Thickness: 0.017"
2.3. Color Code: Black & Red

Element 2: 22 AWG 13 Conductors 7 Strands Tinned Copper PVC

3. Conductor

- 3.1. AWG Size & Stranding: 22 AWG 7 Strands Class B
3.2. Material: Annealed Tinned Copper
3.3. Conductor Count: 13 Conductors

4. Insulation

- 4.1. Material: Polyvinylchloride
4.2. Wall Thickness: 0.010"
4.3. Color Code: Blue, Orange, Yellow, Purple, Brown, Tan, Gray, Pink, Green, White, Green/Black, White/Black, and Red/Black

Overall Assembly

5. Assembly

- 5.1. Nominal Lay Length: 3.75" LHL (3.20 tw/ft)
5.2. Fillers: N/A
5.3. Binder: Tissue Wrap Binder - 100% Coverage

6. Jacket

- 6.1. Material: Polyvinylchloride
6.2. Wall Thickness: 0.040"
6.3. Diameter: 0.335"
6.4. Color: Black
6.5. Ripcord: Yes
6.6. Temperature Rating: -20°C to 80°C
6.7. Weight: 87 Lbs/Mft

7. Markings

- 7.1. Type: N/A
7.2. Legend: N/A
7.3. Footage Markers: N/A

Your signature constitutes that you have read and agreed to this specification sheet and upon confirmation of your order, this item may be non-cancelable and non-returnable.

Signature

Quality Connection
Company



Specification Sheet

Lake Cable Part #: S182C2213CT-NUL

8. Standards

- 8.1. All materials used in the manufacture of this cable are RoHS II & REACH compliant
- 8.2. Maximum Operating Voltage: 300V
- 8.3. Made in the USA

ALL SPECIFIED PARAMETERS ARE NOMINAL AND SUBJECT TO VERIFICATION