


U.I. Lapp GmbH	PRODUCT INFORMATION	
	UNITRONIC® FD CP plus	05.11.2015

Screened highly flexible data transmission cable with PUR outer sheath - UL/CSA-listed

Wide temperature range for applications in harsh climatic environments

Overall braid minimises electrical interference

UL AWM voltage rating 1000V in case of internal wiring allows for internal laying next to power cables with applied UL rating of 1kV

In the USA inside of industrial machines, per NFPA 79, 2015 Ed., 12.9.2 (condition 3 under 12.9.2: Through 1 mm² and <16 AWG), but not inside drag chains or on machines since AWM style is limited to internal wiring

ATTENTION: 3rd condition acc. to NFPA 79, 2015 Ed., 12.9.2, not applicable for this product before May 2016



Single halogen-free cable



Cold-resistant



Mechanical resistance



Oil-resistant



Power chain



Interference signals



Torsion-resistant



Wind Energy


Info

Flexible at low temperatures

Low capacitance

Single halogen-free cable

Product Management	Document: LAPP_PRO240EN.pdf	1 / 4
--------------------	-----------------------------	-------

U.I. Lapp GmbH	PRODUCT INFORMATION	
	UNITRONIC® FD CP plus	05.11.2015

Application range

Multifunctional-use, e.g. for packaging industry and storage and retrieval units
 Suitable for use in measuring, control and regulating circuits
 Drag chain use - in case of horizontal installation travel distances up to 100 m
 For use in drag chains: Please respect the assembly guidelines listed in Appendix T3
 Suitable for torsional applications which are typical for the loop in wind turbine generators (WTG)

Product Make-up

Extra-fine wire strand made of bare copper wires
 Core insulation: Based on Polyolefin
 Non-woven wrapping
 Tinned-copper braiding
 Outer sheath made of special PUR compound
 Outer sheath colour: grey (RAL 7001)

Norm references / Approvals

cULus CMX (Communications Cable listing) acc. to UL 444 and CSA C22.2 No.214, certified by UL (UL file no. for Stuttgart-based U.I. Lapp GmbH: E236660)
 cULus AWM/ Recognized certification (by UL/ UL file no. for Stuttgart-based U.I. Lapp GmbH: E63634): UL AWM Style 21576 acc. to UL 758 and AWM A/B I/II to CSA C22.2 No. 210-11


Product features

Halogen-free, has low capacitance and is flexible down to -40°C
 PUR outer sheath, tear and notch-resistant, resistant to mineral oils and abrasion when used in power chains
 Low-adhesive surface, resistant to hydrolysis and microbes, oil resistant
 Flame retardance ratings: IEC 60332-1-2, VW-1 acc. UL 1581, FT2 (Horizontal Flame Test)
 Designed for 5 up to 10 million bending/unbending cycles (constant flex) in drag chains

Remark

Unless specified otherwise, the shown product values are nominal values. Detailed values (e.g. tolerances) are available upon request.
 Copper price basis: EUR 150/100 kg. Refer to catalogue appendix T17 for the definition and calculation of copper-related surcharges.
 Please find our standard lengths at: www.lappkabel.de/en/cable-standardlengths
 Packaging size: coil ≤ 30 kg or ≤ 250 m, otherwise drum
 Please specify the preferred type of packaging (e.g. 1 x 500 m drum or 5 x 100 m coils).
 Photographs are not to scale and do not represent detailed images of the respective products.

Product Management	Document: LAPP_PRO240EN.pdf	2 / 4
--------------------	-----------------------------	-------

U.I. Lapp GmbH	PRODUCT INFORMATION	
	UNITRONIC® FD CP plus	05.11.2015

Technical Data

Core identification code:	DIN 47100, refer to Appendix T9
Mutual capacitance:	C/C approx. 60 nF/km
Peak operating voltage:	Peak: 250 V (not for power current use or continuous operating voltage to ground above 49VAC or 74VDC)
Classification:	ETIM 5.0 Class-ID: EC000830 ETIM 5.0 Class-Description: Data cable
Inductivity:	approx. 0.65 mH/km
Conductor stranding:	Stranded, extra-fine wire
Torsion movement in WTG:	TW-0 & TW-2, refer to Appendix T0
Minimum bending radius:	Flexing: 7.5 x outer diameter Fixed installation: 4 x outer diameter
Test voltage:	Core/core: 1500 V rms Core/screen: 500 V
Temperature range:	Flexing: -40°C to +80°C Fixed installation: -40°C to +80°C UL/CSA CMX: +75°C UL AWM: +80 °C

Product Management	Document: LAPP_PRO240EN.pdf	3 / 4
--------------------	-----------------------------	-------

UNITRONIC® FD CP plus

05.11.2015

Part number	Number of cores and mm ² per conductor	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
UNITRONIC® FD CP plus				
0028880	2 x 0,14	4.3	11.2	33
0028881	3 x 0,14	4.5	14.1	36
0028882	4 x 0,14	4.8	15.5	40
0028883	5 x 0,14	5.1	18.3	45
0028884	7 x 0,14	5.7	27.8	67
0028885	10 x 0,14	6.7	39.3	87
0028886	14 x 0,14	6.8	45.3	102
0028887	18 x 0,14	7.4	54.1	118
0028888	25 x 0,14	8.9	68.4	157
0028889	2 x 0,25	4.9	14.9	38
0028890	3 x 0,25	5.1	18.8	45
0028891	4 x 0,25	5.5	21.3	52
0028892	5 x 0,25	5.9	31.0	69
0028893	7 x 0,25	6.7	39.6	84
0028894	10 x 0,25	8.2	53.9	109
0028895	14 x 0,25	8.3	64.2	136
0028896	18 x 0,25	9.1	78.4	161
0028897	25 x 0,25	11.0	101.0	213
0028898	2 x 0,34	5.3	18.1	45
0028899	3 x 0,34	5.6	28.7	61
0028900	4 x 0,34	6.0	35.7	77
0028901	5 x 0,34	6.5	39.1	83
0028902	7 x 0,34	7.4	52.7	109
0028903	10 x 0,34	9.1	67.4	147
0028904	14 x 0,34	9.2	85.8	186
0028905	18 x 0,34	10.3	99.7	216
0028906	25 x 0,34	12.5	155.0	314