DATE:	3/28/2007		0035CI	BSS-0CT1				<b>REVISION:</b>	D
	DESCRIPTION: MULTI-COMPONENT COMPOSITE CABLE, DOUBLE SHIELDING, BLACK POLYURETHANE JACKET								]
	CONDUCTORS & COMPONENTS: ONE (1) CAT5E+ (SPECIAL PURCHASED ITEM – BLUE JACKET), ONE (1) PAIR 12 AWG 19/25 TINNED COPPER (.016" NOM PVC), ONE (1) PAIR 22 AWG 7/30 TINNED COPPER (.010" NOM PVC), NINE (9) PAIRS 26 AWG 7/34 TINNED COPPER (.013" NOM PE), FIVE (5) SINGLE CONDUCTORS OF 26 AWG 7/34 TINNED COPPER (.010" NOM PVC) (PAIRS HAVE CUSTOM LAY LENGTHS)								
	CONSTRUCTION:	ISTRUCTION: CONDUCTORS/COMPONENTS CABLED TOGETHER							
	SEPARATOR: TAPE SHIELD:	CLEAR POLYESTER TAPE (.001") ALUMINUM/POLYESTER TAPE (FOIL FACING OUT, 100% COVERAGE, .0012")							
	DRAIN WIRE:YES, BETWEEN TAPE SHIELD AND BRAID SHIELD, #24 7/32 TINNED COPPERBRAID:TINNED COPPER BRAID SHIELD, 70% MINIMUM COVERAGEJACKET:.035" (NOMINAL) SPECIALLY FORMULATED BLACK POLYURETHANE (GLOSS FINISH) .530" NOMINALOPERATING TEMP RANGE:-OC TO +90C								
	COLOR CODE:	22 AWG 26 AWG	12 AWG PAIR: BLACK PAIRED WITH RED   22 AWG PAIR: WHITE PAIRED WITH BROWN   26 AWG PAIRS: PINK PAIRED WITH BROWN, GRAY PAIRED WITH BROWN, VIOLET PAIRED WITH TAN, YELLOW PAIRED WITH GREEN, BLUE PAIRED WITH WHITE, GRAY PAIRED WITH ORANGE, YELLOW PARIED WITH WHITE, TAN PAIRED WITH BROWN, BLUE PAIRED WITH GRAY,   26 AWG SINGLES: TAN, GREEN, VIOLET, WHITE, ORANGE						
	REV LEVEL D:	C: CHAN	B: REMOVED FILLERS (THEY WERE NOT REQUIRED) C: CHANGED JACKET NOTES D: ADD PRETEST PROCEDURES TO SUPPLIED COMPONENT.						
	CHARACTERISTICS (26 AWG 5C SINGLES (26 AWG 9 PAIRS) (22 AWG 1 PAIR) (12 AWG 1 PAIR)	CAPACI 5) 21.0pf/ 16.0pf/ 25.5pf/ 36.0pf/	FT FT FT	RESISTANCE: 40.8 OHMS/M' 40.8 OHMS/M' 16.0 OHMS/M' 1.67 OHMS/M'	INDUCTANG .0685 μΗ/F .0685 μΗ/F .0575 μΗ/F .063 μΗ/FT	T - T 100 OHMS/	E: '1000' +/-10%		
	· · · · · · · · · · · · · · · · · · ·					PART NO:	CT-E3503		
	CAB	LE TEC	HN;	<b>OLOGY, I</b>	<b>NC.</b>	REVISION:	D		
	T   10/4/2016: added     73 RIVER ROAD - WILLINGTON, CT   06279 -   (860) 429 - 7889   FAX (860) 429 - 3615   10/6/2016: filled in information							ROHS COMPLIANT	

customer requested