



Flexible High Impact PA 6D Conduit

Model: **0237.202.048**

Flexible, heavy wall, high cross pressure strength & impact resistance, UL94VO, Highly self-extinguishing, flame retardant, UV resistance, free of silicone, cadmium, halogen, resistant to acids, solvents, oils.

Product Details

| | |
|---------------------|-----------------|
| Manufacture Series | ROHRflex PA 6-D |
| Color | Black |
| Trade Size (in) | 1 1/2" / 2" |
| NW | 48 |
| Size (mm) | 54.5 |
| Profile | fine |
| ID (mm) | 47.5 |
| OD (mm) | 54.5 |
| BR stat. (mm) | 110.0 |
| BR dyn. (mm) | 190.000 |
| BR stat. (in) | 4.33 |
| BR dyn. (in) | 7.480 |
| Temp MIN °C | -40 |
| Temp MAX °C | 115 |
| Temp Short Term °C | 150 |
| Temp MIN °F | -40 |
| Temp MAX °F | 239 |
| Temp Short Term °F | 302 |
| Material | PA6 |
| Flammability | UL94-V0 |
| IP Rating | IP68 |
| Suitable Connectors | FlexaQuick |



"Unsurpassed in Cable Protection and Strain Relief"
2409 Herr St.
Harrisburg, PA 17103