

OLYMPIC WIRE & CABLE CORP.

Toll-Free (800) 526-2269

Fax (973) 227-1606

PRODUCT DATA SHEET

PART NUMBER: 40604

Issued: Tuesday, June 24, 2014

CABLE TYPE: FLEXIBLE CONTROL, OIL RESISTANT

CABLE CONSTRUCTION:

NUMBER OF CONDUCTORS: 4
NUMBER OF PAIRS:
GAUGE: 6
STRANDING: 119/26

CONDUCTOR TYPE:

NICKEL PLATED COPPER:
BARE COPPER: X
TINNED COPPER:
SILVER PLATED COPPER:
ALLOY TYPE:
COPPER CLAD STEEL:
INSULATION MATERIAL: PVC
DIELECTRIC OD_INCHES:
INSULATION THICKNESS: INCHES
COLOR CODE 1: BLACK AND NUMBERED WITH GREEN/YELLOW GROUND

PERFORMANCE:

DC RESISTANCE: OHMS PER MFT AT 20 C
CAPACITANCE: PF PER FT NOM AT 1 KHZ
IMPEDENCE: OHMS + - 15% FROM 1-20 MHZ
NOMINAL VEL OF PROP:
CE COMPLIANT: YES

ATTENUATION MAX DB PER 100 FEET:

MHZ: DB:
MHZ: DB:
MHZ: DB:
MHZ: DB:
MHZ: DB:
MHZ: DB:
MHZ: DB:
MHZ: DB:
MHZ: DB:

FEATURE

COLOR CODE 2:

FILLER:

BARRIER:

SHIELD:

ARMOR:

DRAIN WIRE:

UL STYLE: 21216

MILITARY SPEC:

FLAME TEST: FT-2 VW-1

RoHS COMPLIANT: YES

PRINT LEGEND:

NOTES:

RIP CORD:

JACKET MATERIAL: PVC

JACKET THICKNESS: INCHES

JACKET COLOR: GREY

NOMINAL O.D.: .850 INCHES

CSA STYLE: AWM I/II A/B NEC TYPE:

OPERATING TEMPERATURE: 90 C

VOLTAGE 600 WEIGHT PER 1000FT: 640 LBS

CHINESE RoHS COMPLIANT: BEND RADIUS:

CA PROP 65 (CJ FOR WIRING & CABLE):