


# PRODUCT SPECIFICATION



PRODUCT NUMBER: 0635A9B  
DESCRIPTION: 6 133/ BC 1283

DIAMETER: 0.324  
TOLERANCE +/-: 0.004

GAUGE: 6 AWG  
CONDUCTORS: 1  
STRANDING: 133/0139 BC LHL  
INSULATION: PVC  
VOLTAGE: 600V DC/1000V DC  
TEMPERATURE: 105C  
STYLE: MTW/AWM 1283  
PRINT LEGEND: E517536 6 AWG (13.30mm<sup>2</sup>) (UL) BC-5W2  
or MTW or AWM 1011 80C 600V or AWM  
1015/1028/1232/1283 105C 600V or 1032  
90C 1000V Moisture Resistant VW-  
1—301259 CSA TEW OR AWM I A/B 105C  
600V FT1—SGT2 J1127 (100C) 60V DC



NOM WALL: 0.060  
MINIMUM WALL: 0.054

NOTES: 1. This product meets the requirements of  
SGT per SAE J1127

Tolerances unless otherwise noted: FRACTIONS +/- 1/32, DECIMALS +/- 0.03 (2PL) +/-0.005 (3PL)

Confidential: This drawing and its information are the exclusive and confidential property of Sequel Wire and Cable, LLC and are not to be disclosed, duplicated, distributed, or otherwise used without the written consent of Sequel Wire and Cable, LLC. All rights reserved.

| Date       | Revision | ECN | Description    |
|------------|----------|-----|----------------|
| 12/27/2023 | 2        |     | Added SGT note |