



ATLAS WIRE, LLC
 1601 GLENLAKE AVENUE
 ITASCA, IL 60143
 (847) 678-1210
 (847) 678-1281 FAX
 www.atlaswirecorp.com



Atlas Wire, LLC
 Registered to ISO9001 and TS16949
 Itasca, IL 60176
 Reference No. 10000854
 Tucson, AZ 85714
 Reference No. 10003647

MATERIAL SPECIFICATION SHEET

**#08 133/29 TINNED COPPER 3/64" PVC
 RoHS COMPLIANT**

**MACHINE TOOL WIRE 600v N.E.C. STANDARD BC-5W2 OR
 AWM STYLES 1028/1231/1015/1344 105c 600v OR
 AWM 1032 90c 1000v OR AWM 1336 90c 600v VW1
 CSA TEW OR AWM I A/B 105c 600v OIL & WATER RESISTANT 75c FT1**

CONDUCTOR:	#08 133/29 TINNED COPPER CONDUCTOR	
	NOMINAL O.D.	.161"
	APPROXIMATE CIRCULAR MILL AREA	16,500
	WEIGHT PER THOUSAND FEET	51.00#
	BASIC SPECIFICATION	ASTM B 173
PVC:	TEMPERATURE RATING	105c
	VOLTAGE RATING	600 VOLTS
	ELONGATION	320% AVERAGE
	TENSILE STRENGTH	2450 PSI AVERAGE
	SPECIFIC GRAVITY	1.34
	DUROMETER (SHORE)	85 (A)
	OXYGEN INDEX	25
	BRITTLE POINT	-25c
	SPARK TESTED	12,500 VOLTS
	NOMINAL O.D.	.260"
	WEIGHT PER THOUSAND FEET	70.25#
USE:	INTERNAL WIRING OF APPLIANCES WHERE EXPOSED TO TEMPERATURES NOT EXCEEDING 105 DEG C: OR WHERE EXPOSED TO OIL AT A TEMPERATURE NOT EXCEEDING 60 DEG C. MOISTURE RESISTANT 60C. 2500 VOLTS PEAK – FOR ELECTRONIC USE ONLY.	

info@atlaswirecorp.com

Revision 10-30-17