




Nylon Strain Relief
Nickel Plated Brass
PVDf / Steel
Accessories
Adapter, Reducer, Enlarger
Conduit System
Technical Information
Other Products / Index

Dome Plugs: Nylon

Part Numbers		Thread Type & Size	Dimensions in Inches (mm)		
			H	D	E
-40 °F to 212 °F (-40 °C to 100 °C)		See page 49 for thread specs	Overall Height	Dome Diameter	Thread Length
					
DP-07-BK	DP-07-GY	PG 7	.31 (8)	.59 (15)	.24 (6)
DP-09-BK	DP-09-GY	PG 9	.35 (9)	.75 (19)	.24 (6)
DP-11-BK	DP-11-GY	PG 11	.35 (9)	.87 (22)	.24 (6)
DP-13-BK	DP-13-GY	PG 13 / 13.5	.37 (9.5)	.98 (25)	.24 (6)
DP-16-BK	DP-16-GY	PG 16	.37 (9.5)	1.06 (27)	.24 (6)
DP-21-BK	DP-21-GY	PG 21	.43 (11)	1.30 (33)	.31 (8)
DP-29-BK	DP-29-GY	PG 29	.47 (12)	1.73 (44)	.31 (8)
DP-36-BK	DP-36-GY	PG 36	.59 (15)	2.17 (55)	.39 (10)
DP-42-BK	DP-42-GY	PG 42	.63 (16)	2.44 (62)	.39 (10)
DP-48-BK	DP-48-GY	PG 48	.63 (16)	2.72 (69)	.47 (12)
DM-12-BK	DM-12-GY	M12 x 1.5	.39 (10)	.59 (15)	.24 (6)
DM-16-BK	DM-16-GY	M16 x 1.5	.45 (11.5)	.79 (20)	.28 (7)
DM-20-BK	DM-20-GY	M20 x 1.5	.37 (9.5)	.98 (25)	.24 (6)
DM-25-BK	DM-25-GY	M25 x 1.5	.61 (15.5)	1.18 (30)	.43 (11)
DM-32-BK	DM-32-GY	M32 x 1.5	.63 (16)	1.50 (38)	.43 (11)
DM-40-BK	DM-40-GY	M40 x 1.5	.71 (18)	1.81 (46)	.51 (13)
DM-50-BK	DM-50-GY	M50 x 1.5	.73 (18.5)	2.20 (56)	.51 (13)
DM-63-BK	DM-63-GY	M63 x 1.5	.75 (19)	2.72 (69)	.59 (15)



Nylon Dome Plug


Also available with the following approvals:



www.sealconex.com




Note: HP & HM Nylon Plugs can be tightened with Hex & Allen wrenches, as well as regular screwdrivers.




Nylon Hex Plug

Hex Plugs: Nylon



Part Numbers		Thread Type & Size	Dimensions in Inches (mm)		
			H	X	E
-4 °F to 176 °F (-20 °C to 80 °C)		See page 49 for thread specs	Overall Height	Wrench Flat	Thread Length
					
HP-07-BK	PG 7 / 1/4" NPT	.51 (13)	.59 (15)	.33 (8.5)	
HP-09-BK	PG 9	.51 (13)	.75 (19)	.33 (8.5)	
HP-11-BK	PG 11	.57 (14.5)	.94 (24)	.35 (9)	
HP-13-BK	PG 13 / 13.5	.57 (14.5)	.94 (24)	.35 (9)	
HP-16-BK	PG 16	.63 (16)	1.10 (28)	.41 (10.5)	
HP-21-BK	PG 21	.69 (17.5)	1.42 (36)	.45 (11.5)	
HP-29-BK	PG 29	.71 (18)	1.81 (46)	.45 (11.5)	
HP-36-BK	PG 36	.79 (20)	2.17 (55)	.53 (13.5)	
HP-42-BK	PG 42	.79 (20)	2.36 (60)	.53 (13.5)	
HP-48-BK	PG 48	.83 (21)	2.76 (70)	.57 (14.5)	
HM-12-BK	M12 x 1.5	.51 (13)	.59 (15)	.33 (8.5)	
HM-16-BK	M16 x 1.5	.51 (13)	.75 (19)	.33 (8.5)	
HM-20-BK	M20 x 1.5	.57 (14.5)	.94 (24)	.35 (9)	
HM-25-BK	M25 x 1.5	.63 (16)	1.10 (28)	.41 (10.5)	
HM-32-BK	M32 x 1.5	.69 (17.5)	1.42 (36)	.45 (11.5)	
HM-40-BK	M40 x 1.5	.71 (18)	1.81 (46)	.45 (11.5)	
HM-50-BK	M50 x 1.5	.79 (20)	2.17 (55)	.53 (13.5)	
HM-63-BK	M63 x 1.5	.83 (21)	2.76 (70)	.57 (14.5)	

Hex Plugs: Polypropylene

Part Numbers		Thread Type & Size	Dimensions in Inches (mm)		
			H	X	E
0 °C to 135 °C (32 °F to 275 °F)		See page 49 for thread specs	Overall Height	Wrench Flat	Thread Length
					
HN-38-BK	3/8" NPT	.83 (21)	.75 (19)	.59 (15)	
HN-12-BK	1/2" NPT	.81 (20.5)	.94 (24)	.55 (14)	
HN-34-BK	3/4" NPT	.87 (22)	1.10 (28)	.63 (16)	
HN-10-BK	1" NPT	.91 (23)	1.34 (34)	.67 (17)	



Accessories - (Dome) Hole Plugs
Nickel Plated Brass - PG/Metric Threads

Dome Plugs: Nickel Plated Brass

Part Numbers		Thread Type & Size	Dimensions in Inches (mm)			
			H	D	E	E
-40 °F to 176 °F (-40 °C to 80 °C)		See page 49 for thread specs	Overall Height	Dome Diameter	Thread Length	Thread Length w/ O-Ring
						
DP-07-BR	DP-07-BR-B	PG 7	.31 (8)	.55 (14)	.20 (5)	.19 (4.8)
DP-09-BR	DP-09-BR-B	PG 9	.35 (9)	.67 (17)	.24 (6)	.22 (5.5)
DP-11-BR	DP-11-BR-B	PG 11	.35 (9)	.79 (20)	.24 (6)	.22 (5.5)
DP-13-BR	DP-13-BR-B	PG 13 / 13.5	.37 (9.5)	.87 (22)	.26 (6.5)	.24 (6)
DP-16-BR	DP-16-BR-B	PG 16	.37 (9.5)	.94 (24)	.26 (6.5)	.24 (6)
DP-21-BR	DP-21-BR-B	PG 21	.43 (11)	1.18 (30)	.28 (7)	.26 (6.5)
DP-29-BR	DP-29-BR-B	PG 29	.47 (12)	1.54 (39)	.31 (8)	.30 (7.5)
DP-36-BR	DP-36-BR-B	PG 36	.59 (15)	1.97 (50)	.35 (9)	.35 (9)
DP-42-BR	DP-42-BR-B	PG 42	.63 (16)	2.24 (57)	.39 (10)	.39 (10)
DP-48-BR	DP-48-BR-B	PG 48	.63 (16)	2.52 (64)	.39 (10)	.39 (10)

O-Ring needed for Nema 4x.

Dome Plugs: Nickel Plated Brass

Part Numbers		Thread Type & Size	Dimensions in Inches (mm)					
			H	D	E	H	D	E
-40 °F to 176 °F (-40 °C to 80 °C)		See page 49 for thread specs	Overall Height	Dome Diameter	Thread Length	Overall Height w/ O-Ring	Dome Diameter w/ O-Ring	Thread Length w/ O-Ring
								
DM-12-BR	DM-12-BR-B	M12 x 1.5	.30 (7.5)	.55 (14)	.20 (5)	.37 (9.5)	.55 (14)	.26 (6.5)
DM-16-BR	DM-16-BR-B	M16 x 1.5	.35 (9)	.71 (18)	.20 (5)	.35 (9)	.79 (20)	.24 (6)
DM-20-BR	DM-20-BR-B	M20 x 1.5	.37 (9.5)	.87 (22)	.26 (6.5)	.37 (9.5)	.94 (24)	.26 (6.5)
DM-25-BR	DM-25-BR-B	M25 x 1.5	.43 (11)	1.10 (28)	.28 (7)	.43 (11)	1.10 (28)	.28 (7)
DM-32-BR	DM-32-BR-B	M32 x 1.5	.47 (12)	1.38 (35)	.31 (8)	.49 (12.5)	1.38 (35)	.31 (8)
DM-40-BR	DM-40-BR-B	M40 x 1.5	.51 (13)	1.73 (44)	.33 (8.5)	.47 (12)	1.77 (45)	.31 (8)
DM-50-BR	DM-50-BR-B	M50 x 1.5	.59 (15)	2.13 (54)	.35 (9)	.59 (15)	2.17 (55)	.35 (9)
DM-63-BR	DM-63-BR-B	M63 x 1.5	.63 (16)	2.64 (67)	.39 (10)	.63 (16)	2.68 (68)	.39 (10)



To order hole plug with a FPM O-Ring instead of Buna-N, replace "-V" (FPM) to part number (e.g. DP-11-BR-V)

For Material Specifications and Approval Information, please refer to page 45.