



US North Central
 5001 S. Towne Drive
 New Berlin, WI 53151
 800-344-2323
www.IEWC.com

Specification

Issue Date: 10/29/2013

Issue: 1

Construction

Description:	3 Cond 18(16) PVC/PVC			Diam. (In)												
Component:	3 Conductors															
Conductor:	18 16/30 TC to ASTM B 33-74			0.048"												
Insulation:	0.01"	Premium Grade PVC		0.068"												
Color Code:	<table border="1" style="width: 100%; text-align: center;"> <thead> <tr> <th>Cond</th> <th>Color</th> <th>Cond</th> <th>Color</th> <th>Cond</th> <th>Color</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>Brown</td> <td>2</td> <td>Lt Blue</td> <td>3</td> <td>Green/Yellow</td> </tr> </tbody> </table>				Cond	Color	Cond	Color	Cond	Color	1	Brown	2	Lt Blue	3	Green/Yellow
Cond	Color	Cond	Color	Cond	Color											
1	Brown	2	Lt Blue	3	Green/Yellow											
Assembly:	3 Conductors Bunched Cabled			0.1462"												
Tape:	Optional Non-Woven Separator Tape for Strip-Ability			0.1462"												
Jacket:	0.032"	AWM Jacket Compound		0.2102"												
Jacket Color:	Gray			0.2102"												
Print:	E174416 RU AWM 2464 80C 300V VW-1 cUR AWM IA 80C 300V ROHS															
Specifications:	<p>UL AWM - 2464 80°C 300 Volt VW-1</p> <p>Canadian cUL AWM - 2464 80°C 300 Volt FT-1</p>															
Environmental Compliance	<p>EU Directive 2002/95/EC(RoHS): All materials used in the manufacture of this part are in compliance with EU Directive 2002/95/EU regarding the restriction of use of certain hazardous substances in electrical and electronic equipment.</p> <p>REACH Regulation (EC 1907/2006): This product does not contain Substances of Very High Concern (SVHC) listed on the European Union's REACH candidate list in excess of 0.1% mass of the item.</p> <p>California Prop 65: The outer surface materials used in the manufacture of this part meet the requirements of California Prop. 65.</p>															