



Description: Four Conductor Composite Cable
 Overall TPE Jacket

Date: 2/5/2014

JM Part Number: JM57136
Reference: 1000054

Components

Component A: Three 4 AWG Insulated Conductors

Conductor: 4 AWG, 413/30 bare copper
 Insulation: .063" nominal wall of TPE (see color code) .392"

Component B: One 18 AWG Insulated Conductor

Conductor: 18 AWG, 16/30 bare copper
 Insulation: .032" nominal wall of TPE (see color code) .109"

Overall Cable Construction

Cabling: Three A Components and One B Component
 FRPP fillers, as necessary, for roundness

Binder: Fleece tape

Jacket: .145" nominal wall of Black TPE 1.137"

Print

**E466343 4 AWG (20.9 MM²)/3C + 18 AWG (0.81 MM²)/1C (UL) EVE -50C TO 105C DRY 60C WET
 600V WATER RESISTANT - FOR USE WITH ELECTRIC VEHICLES**

Color Code

Component A: Black Red Green

Component B: Purple

Requirements

Temperature: -50C to 105C Dry 60C Wet Approvals: UL Type EVE
 Voltage: 600V

Handwritten signature: DuBose 2/24/14

Written By:	rjc	2/5/2014	Rev. 0	Initial Issue
Revised By:	rjc	2/18/2014	Rev. 1	Revised Color Code, Added UL File No. to print, Removed "pending" from approvals
Revised By:				
Revised By:				
Revised By:				