



Confidential
Price Agreement

REV.BV
EUA: 1000225

CUSTOMER NAME IEWC NEW BERLIN
CUSTOMER NUMBER 6520
LOCATION 5001 SOUTH TOWNE DRIVE, NEW BERLIN, WI
END USER ROCKWELL / ELECTROL/ALLEN BRADLEY/RELIANCE
AGREEMENT BEGIN DATE July 3, 2024
AGREEMENT END DATE October 7, 2024
QUOTED CURRENCY USD
CHANNEL ACCOUNT MANAGER Jack Strum
CHANNEL MANAGER Amy Draudt

Jeremy Sadler / chris.hartman@belden.com
MKT.Contact / PRI.CONTACT

PRICES ON THIS AGREEMENT ARE SHIP AND DEBIT ONLY, SYSTEM PRICES ARE NOT CHANGED AT TIME OF ORDER SHIP AND DEBIT PRICING DOES NOT APPLY TO SPECIAL DESIGNS PRICES ARE GOOD ONLY FOR THE FOLLOWING END USER: ROCKWELL/ELECTROL/ALLEN BRADLEY/RELIANCE

Table with columns: S&D CODE, DESCRIPTION, CUST. ITEM, COMMIT QTY., PUTUP, ORD INC QTY., PRICE PER UOM, UOM, PRICE PER UNIT. Contains multiple rows of product specifications and pricing.

Y	37506	EPDM is naturally corona and more heat resistant than many other rubber compounds and is able to take longer bake cycles frequently needed for big jobs. EPDM has superior weather resistance and low temperature pliability.	1000	1000	1000	\$2.2725	FT	\$2.2725
Y	37508	EPDM is naturally corona and more heat resistant than many other rubber compounds and is able to take longer bake cycles frequently needed for big jobs. EPDM has superior weather resistance and low temperature pliability.	1000	1000	1000	\$1.6324	FT	\$1.6324
Y	8770	18 AWG stranded (16x30) tinned copper conductors, conductors cabled, polyethylene insulation, overall Beldfoil® shield (100% coverage), 20 AWG stranded tinned copper drain wire, PVC jacket.	2	1000	1	\$590.6050	EA	\$0.5906
Y	8761	22 AWG stranded (7x30) TC conductors, polyethylene insulation, twisted pair, overall Beldfoil® shield (100% coverage), 22 AWG stranded TC drain wire, PVC jacket.	1	1000	1	\$422.4177	EA	\$0.4224
Y	8669	Shielding and Bonding Cable.	32	250	1	\$977.3275	EA	\$3.9093
Y	39114	14 AWG stranded (41x30) tinned copper conductor, PPO insulation. Rated 105°C, 600V. Rated 2500V peak for electronic circuits, and internal wiring of electronic and electrical equipment.	1	1000	1	\$1,326.5051	EA	\$1.3265
Y	39120	20 AWG stranded (10x30) tinned copper conductor, PPO insulation. Rated 105°C, 600V. Rated 2500V peak for electronic circuits, and internal wiring of electronic and electrical equipment	1	1000	1	\$429.2579	EA	\$0.4293
Y	1031A	16 AWG triads stranded (7x24) bare copper conductors, twisted triads, overall Beldfoil shield (100% coverage), PVC insulation, PVC jacket.	5000	5000	5000	\$0.4637	FT	\$0.4637
Y	9366	16 AWG triads stranded (19x29) tinned copper conductors, twisted triads, overall Beldfoil® shield (100% coverage), PVC insulation, PVC jacket.	1	1000	1	\$1,720.3961	EA	\$1.7204
Y	9316	16 AWG pairs stranded (19x29) tinned copper conductors, twisted pairs, PVC insulation, overall Beldfoil® shield (100% coverage), PVC jacket.	1000	1000	1000	\$1.2294	FT	\$1.2294
Y	9411	14 AWG pairs stranded (42x30) tinned copper conductors, twisted pairs, unshielded, PVC insulation, PVC jacket.	1	1000	1	\$1,478.8215	EA	\$1.4788
Y	8916	14 AWG stranded (41x30) tinned copper conductor, PVC insulation. Rated 105°C, 600V. Rated 2500V peak for electronic circuits, and internal wiring of electronic and electrical equipment.	7	500	1	\$369.5384	EA	\$0.7391
Y	8663	Shielding and Bonding Cable.	1	250	0	\$651.4566	EA	\$2.6058
Y	8662	Shielding and Bonding Cable.	1	250	1	\$1,927.2239	EA	\$7.7089
Y	9841	24 AWG stranded (7x32) TC conductors, polyethylene insulation, twisted pairs, overall Beldfoil® (100% coverage) + TC braid shield (90% coverage), 24 AWG stranded TC drain wire, PVC jacket.	6	1000	1	\$1,050.9787	EA	\$1.0510
Y	9873	20 AWG stranded (7x28) TC conductors, polypropylene insulation, twisted pairs, individually shielded w/Beldfoil® (100% coverage), 22 AWG stranded TC drain wire, overall PVC jacket.	3	1000	1	\$1,597.5517	EA	\$1.5976
Y	9444	Electronic, 4 Conductor 20AWG (7x28) Tinned Copper, PVC Insulation, PVC Outer Jacket, CMG	4	1000	1	\$762.8846	EA	\$0.7629
Y	9260	Electronic, 6 Conductor 20AWG (7x28) Tinned Copper, PVC Insulation, Overall Tinned Copper Braid(85%) Shield, PVC Outer Jacket, CMG	2	1000	1	\$3,802.8579	EA	\$3.8029
Y	3106A	RS-485, 1 Pair 22AWG (7x30) Tinned Copper, PO Insulation, Individually Beldfoil®, 1 conductor 22AWG (7x30) Tinned Copper, PVC Insulation, Overall Tinned Copper Braid(65%) Shield, PVC Outer Jacket, CM	1000	1000	1000	\$1.5301	FT	\$1.5301
Y	8479	Portable Cordage, 3 Conductor 14AWG (41x30) Bare Copper, EPDM Insulation, Rubber Outer Jacket, UL Type SJ	12	250	1	\$677.8329	EA	\$2.7113
Y	9954	Electronic, 4 Conductor 16AWG (19x29) Tinned Copper, PVC-NYL Insulation, Overall Tinned Copper Braid(90%) Shield, PVC Outer Jacket	1	1000	1	\$4,654.2030	EA	\$4.6542
Y	9721	Electronic, 8 Conductor 16AWG (19x29) Tinned Copper, PVC Insulation, PVC Outer Jacket	1	1000	1	\$4,200.3754	EA	\$4.2004
Y	9407	High Performance Instrumentation, 1 Pair 22AWG (7x30) Tinned Copper, PVC Insulation E2 Color Code, PVC Outer Jacket, PLTC-ER	1	1000	1	\$523.6371	EA	\$0.5236
Y	9773	Audio, Control & Instrument Cable, 18 AWG stranded (19x30) tinned copper conductors, polypropylene insulation, twisted pairs, individually shielded with Beldfoil® (100% coverage), 20 AWG stranded tinned copper drain wire, PVC jacket.	1	1000	1	\$2,182.7673	EA	\$2.1828
Y	37102	Rubber Lead Wire, 2AWG (163x24) Tinned Copper, EPDM Insulation, AWM 3340 AWM 3374 CSA TYPE CL1254 600V 125C FLEX 150C NO FLEX	1000	1000	1000	\$2.8851	FT	\$2.8851
Y	FP1LDLD003M	FX PATCH CORD, OM1, LC DUPLEX - LC DUPLEX, 3 M, OFNR, DUPLEX ZIP 2.0 MM, A-TO-B, ORANGE JACKET	1	1	1	\$18.7497	EA	
Y	FP1LDLD005M	FX PATCH CORD, OM1, LC DUPLEX - LC DUPLEX, 5 M, OFNR, DUPLEX ZIP 2.0 MM, A-TO-B, ORANGE JACKET	1	1	1	\$20.6305	EA	
Y	37100	Rubber Lead Wire, 2/0AWG (504x26) Tinned Copper, EPDM Insulation, AWM 3340 AWM 3374 CSA TYPE CL1254 600V 125C FLEX 150C NO FLEX	100	100	100	\$7.3720	FT	\$7.3720
Y	8762 0601000	Electronic, 2 Conductor 20AWG (7x28) Tinned Copper, PE Insulation, Overall Beldfoil® Shield, PVC Outer Jacket, CM, Suitable for Audio, Control, and Instrumentation Applications	6	1000	1	\$882.2162	EA	\$0.8822
* Y	37106 010100	Rubber Lead Wire, 6AWG (84x25) Tinned Copper, EPDM Insulation, AWM 3340 AWM 3374 CSA TYPE CL1254 600V 125C FLEX 150C NO FLEX	100	100	100	\$1.4580	FT	\$1.4580

* Denotes Change

§ Denotes Promotion