



AE3478


Specification Sheet

Lake Cable Part #: S183CT(16)-NUL


Description: 18 AWG 3 conductors constructed with 16 strands tinned copper wires, PVC insulation, and an overall PVC jacket

- 1. **Conductor**
 - 1.1. AWG Size & Stranding: 18 AWG 16 Strands
 - 1.2. Material: Annealed Tinned Copper
 - 1.3. Conductor Count: 3 Conductors
- 2. **Insulation**
 - 2.1. Material: Polyvinylchloride
 - 2.2. Wall Thickness: 0.015"
 - 2.3. Color Code: Black, Red & Green
- 3. **Assembly**
 - 3.1. Cable Lay Length: 2.25" LHL (5.33 tw/ft), Nominal
 - 3.2. Cable Binder: Tissue Wrap - 100% Coverage
- 4. **Jacket**
 - 4.1. Material: Polyvinylchloride Pressure Jacket
 - 4.2. Wall Thickness: 0.035"
 - 4.3. Diameter: 0.247" ± 0.005"
 - 4.4. Color: Black
 - 4.5. Ripcord: N/A
 - 4.6. Temperature Rating: -20°C to 80°C
 - 4.7. Weight: 45 Lbs/Mft
- 5. **Markings**
 - 5.1. Type: N/A
 - 5.2. Legend: N/A
 - 5.3. Footage Markers: N/A
- 6. **Standards**
 - 6.1. All materials used in the manufacture of this cable are RoHS II & REACH compliant
 - 6.2. Maximum Operating Voltage: 300V
 - 6.3. Made in the USA

Your signature constitutes that you have read and agreed to this specification sheet and upon confirmation of your order, this item may be non-cancelable and non-returnable.



 Signature



 Quality Connection
 Company

ALL SPECIFIED PARAMETERS ARE NOMINAL AND SUBJECT TO VERIFICATION