



SPECIFICATION SHEET

Phone: 888- ELECTRO or 613-394-4896
Fax: 613-394-4101 email: info@electrocables.com
Mailing: P.O. Box 276, Trenton, ON K8V 5R5
www.electrocables.com

5-Feb-2014

Product Number : 5152003TFT4.2

RoHS

**O/A SH CABLE 3/C 20/7 AWG STC
SR-PVC Insulation
PVC FT-4 Jacket**

Conductor : 20 AWG 7 Strand STC Cond.	
Total Cable Weight : 45 kg/km	Final Diameter : 0.225 inches
Insulation : SR-PVC	Jacket : PVC
Shield : Foil Shield 0.75	
Drain : 20 AWG 7 Strand STC Cond.	
DC Resistance 25°C: 10.3 Ohms / 1000 ft	Mutual Capacitance : 35.3 pF/ft
Impedance : 60 Ohms	Cond to Shield Cap. : 65.3 pF/ft
Velocity of Prop : 59 %	Inductance. : 1.3 mH/km

Print Notes :

Standard Print : ECI CSA CMG 105°C OR AWM II A/B 105°C LL61365 300V FT-4 RU AWM
E107863 STYLE 2464 300V VW-1 20 AWG RoHS

(All of the above values are approximated to within +/- 10%)