

Nonmetallic Cable

Two Screw, Strap Type Connectors



566-DC2



660-DC2 thru
666-DC2



650-DC2 thru
676-DC2


For connecting nonmetallic cable to box or enclosure.

566-DC2 & 650-DC2 can be used for one or two 14/2 or 12/2 NM-B cables or one 14/2 through 10/3 NM-B cable.

The 650-DC2 is also listed for use with 18/3 to 12/3 SJO cord. The 650-HD2 has a die cast strap for heavy duty use and is listed for use with 16/2 to 14/3 SJO cord.

 File No. E20534: 566-DC2

 File No. E11698: 650-DC2, 651SP, 650-HD2

 File No. E15123: 660-DC2 thru 666-DC2;
670-DC2 thru 676-DC2

 File No. LR39354: 650-DC2, 660-DC2, 670-DC2

Zinc Die Cast - Round Cable

Catalog Number	K.O. Size	Nonmetallic Cable Range		Unit Qty.	Std. Pkg. Qty.
		Min.	Max.		
566-DC2	1/2"	14/2	or larger	100	1000
660-DC2	3/4"	.680"	.800"	25	250
662-DC2	1"	.850"	1.000"	10	100
664-DC2	1 1/4"	1.090"	1.300"	10	100
665-DC2	1 1/2"	1.187"	1.490"	---	25
666-DC2	2"	1.750"	1.950"	---	25

Zinc Die Cast - Oval Cable

Catalog Number	K.O. Size	Oval Service Cable Size		Unit Qty.	Std. Pkg. Qty.
		Height	Width		
650-DC2	1/2"	.250"	.500"	100	1000
650-HD2	1/2"	.250"	.500"	100	1000
670-DC2	3/4"	.437"	.625"	25	250
672-DC2	1"	.500"	.750"	10	100
674-DC2	1 1/4"	.625"	1.062"	10	100
675-DC2	1 1/2"	.750"	1.250"	---	25
676-DC2	2"	1.062"	1.625"	---	25