

Straight Blade Devices

INDUSTRIAL



30A, 50A, 60A | Power Devices

30A, 50A and 60A Industrial Grade Power Devices

3-Pole, 4-Wire, Grounding

Rating	30A-125/250V		
NEMA			
	14-30R	14-30P	
Description	Cat. No.	Cat. No.	Wallplate Information
Flush Mount Receptacle	278	—	Fits all wallplates with 2.15" diameter center hole
Panel Mount Receptacle	278-PM	—	Fits all wallplates with 2.15" diameter center hole
Surface Mount Receptacle	55054	—	Fits all wallplates with 2.15" diameter center hole
Angle Plug	—	9432-P	



279-PM

Rating	50A-125/250V		
NEMA			
	14-50R	14-50P	
Description	Cat. No.	Cat. No.	Wallplate Information
Flush Mount Receptacle	279	—	Fits all wallplates with 2.15" diameter center hole
Panel Mount Receptacle	279-PM	—	Fits all wallplates with 2.15" diameter center hole
Surface Mount Receptacle	55050	—	Fits all wallplates with 2.15" diameter center hole
Angle Plug	—	9452-P	



55050

Rating	60A-125/250V		
NEMA			
	14-60R	14-60P	
Description	Cat. No.	Cat. No.	Wallplate Information
Flush Mount Receptacle	9460	—	Fits all wallplates with 2.465" diameter center hole
Flush Mount Receptacle, Isolated Ground	9460-IG	—	Fits all wallplates with 2.465" diameter center hole
Angle Plug	—	9462-P	



9460

3-Pole, 4-Wire, 3 Phase, Grounding

Rating	30A-250V 3Ø		
NEMA			
	15-30R	15-30P	
Description	Cat. No.	Cat. No.	Wallplate Information
Flush Mount Receptacle	8430	—	Fits all wallplates with 2.465" diameter center hole
Angle Plug	—	8432-P	



8430

Rating	50A-250V 3Ø		
NEMA			
	15-50R	15-50P	
Description	Cat. No.	Cat. No.	Wallplate Information
Flush Mount Receptacle	8450	—	Fits all wallplates with 2.465" diameter center hole
Flush Mount Receptacle, Isolated Ground	8450-IG	—	Fits all wallplates with 2.465" diameter center hole
Angle Plug	—	8452-P	



8452-P

Continued on next page