



ATLAS WIRE LLC.  
 9525 RIVER STREET  
 SCHILLER PARK, ILLINOIS 60176  
 (847) 678-1210  
 (847) 678-1281 FAX  
 www.atlaswirecorp.com



Atlas Wire, LLC  
 Registered to ISO9001 and TS16949  
 Schiller Park, IL 60176  
 Reference No. 10000854  
 Tucson, AZ 85714  
 Reference No. 10003647

## MATERIAL SPECIFICATION SHEET

**#24 7/32 OVERCOAT 1/64" PVC**  
**RoHS COMPLIANT**  
**AWM STYLE 1569 105c-300v**  
**AWM STYLE 1007 80c-300v OR**  
**CSA TR 64 90c OR CSA AWM 1 A/B 105c-300v**

<b>CONDUCTOR:</b>	#24 7/32 OVERCOAT CONDUCTOR 3/8" LAY	
	NOMINAL O.D.	.024"
	APPROXIMATE CIRCULAR MILL AREA	442
	WEIGHT PER THOUSAND FEET	1.50#
	BASIC SPECIFICATION	ASTM B 470 TYPE III
<b>PVC:</b>	TEMPERATURE RATING	UL1007 90c UL1569 105c
	VOLTAGE RATING	300v
	ELONGATION	330% AVERAGE
	TENSILE STRENGTH	2450 PSI AVERAGE
	SPECIFIC GRAVITY	1.32
	DUROMETER (SHORE)	91 (A)
	OXYGEN INDEX	28
	BRITTLE POINT	-24c
	SPARK TESTED	7,100 VOLTS
	WALL THICKNESS	.016"
	FINISHED OD	.056"
	WEIGHT PER THOUSAND FEET	2.71#
<b>USE:</b>	INTERNAL WIRING OF APPLIANCES; OR WHERE EXPOSED TO OIL AT TEMPERATURES NOT EXCEEDING 60C OR 80C. WHERE NOT SUBJECTED TO MOVEMENT OR MECHANICAL DAMAGE . 600V PEAK FOR ELECTRONIC USE ONLY.	