

UL 10086 (continued)

| Catalog Number | Size (AWG) | Stranding (No./AWG) | Insulation Thickness (mils) | Overall Diameter (inches) | Weight (lbs/1000 ft) | Part Number | |
|----------------|------------|---------------------|-----------------------------|---------------------------|----------------------|-------------|--------|
| | | | | | | U.S. | Canada |
| TZ10086-181T | 18 | 1/18 | 10 | .060 | 6 | - | 2421 |
| TZ10086-187T | 18 | 7/26 | 10 | .069 | 6.5 | - | 2422 |
| TZ10086-1819S | 18 | 19/30 | 10 | .067 | 7 | - | 2423 |
| TZ10086-161T | 16 | 1/16 | 10 | .071 | 9 | - | 2424 |
| TZ10086-167T | 16 | 7/.0192" | 10 | .078 | 10 | - | 2425 |
| TZ10086-1619S | 16 | 19/.0117" | 10 | .076 | 10 | - | 2426 |
| TZ10086-141T | 14 | 1/14 | 10 | .084 | 14 | - | 2427 |
| TZ10086-147T | 14 | 7/.0242" | 10 | .092 | 15 | - | 2428 |
| TZ10086-1419S | 14 | 19/.0147" | 10 | .089 | 16 | - | 2429 |
| TZ10086-121T | 12 | 1/12 | 15 | .111 | 23 | - | 2430 |
| TZ10086-1219T | 12 | 19/.0185" | 15 | .119 | 23 | - | 2431 |
| TZ10086-1237S | 12 | 37/.0133" | 15 | .123 | 24 | - | 2432 |
| TZ10086-1019T | 10 | 19/.0234" | 15 | .143 | 37 | - | 2433 |
| TZ10086-1037T | 10 | 37/.0167" | 15 | .145 | 34 | - | 2434 |
| TZ10086-10105S | 10 | 105/30 | 15 | .154 | 36 | - | 2435 |
| TZ10086-819T | 8 | 19/.0295" | 30 | .201 | 63 | - | 2436 |
| TZ10086-8133S | 8 | 133/29 | 30 | .220 | 65 | - | 2437 |
| TZ10086-619T | 6 | 19/.0372 | 30 | .241 | 96 | - | 2438 |
| TZ10086-6133S | 6 | 133/27 | 30 | .262 | 99 | - | 2439 |
| TZ10086-4133T | 4 | 133/25 | 30 | .325 | 150 | - | 2440 |
| TZ10086-2133T | 2 | 133/23 | 30 | .395 | 231 | - | 2441 |
| TZ10086-1259T | 1 | 259/25 | 45 | .462 | 304 | - | 2442 |
| TZ10086-01259T | 1/0 | 259/24 | 45 | .514 | 375 | - | 2443 |
| TZ10086-02259T | 2/0 | 259/23 | 45 | .567 | 466 | - | 2444 |
| TZ10086-03259T | 3/0 | 259/22 | 45 | .620 | 579 | - | 2445 |
| TZ10086-04259T | 4/0 | 259/21 | 45 | .676 | 722 | - | 2446 |

¹Suffix "S" on Catalog Number denotes silver plated copper; suffix "T", tin plated copper.

All figures referenced are nominal.

