

1. CONDUCTOR:

- 1.1 Size and Material: 16 19/.0117" AWG tin-plated copper wire.
- 1.2 O.D.: .0565" nom.

2. INSULATION:

- 2.1 Extruded special ETFE (Tefzel® 750).
- 2.2 Marking on the insulation: as per UL and CSA Standards.
- 2.3 O.D.: .0765" ± .002"
- 2.4 Color: as per order (replace X in the part number and the description by 0-9 color code).

3. PERFORMANCE:

- 3.1 Voltage rating: 600 VAC R.M.S.
- 3.2 Temperature rating: 150°C




4. REFERENCES:

- 4.1 UL Subject 758 (AWM), Style 10086.
- 4.2 CSA Standard C22.2 No.210.2 (AWM), Class I Group A/B.

CUSTOMER APPROVAL

Sign: _____

Date: _____

Engineering Change Notice No.								 <p>This specification is the property of Harbour Industries Canada Limited and may not be used or copied without the express written permission of Harbour Industries Canada Limited.</p>		Done: <i>Pierre Garand</i>		 <p>1365, boul. Industriel, Farnham, Quebec, Canada, J2N 2X3 Phone: (450) 293-5304 Fax: (450) 293-2421 Web site: www.harbourfd.com</p>							
										Date: January 17, 2014									
										Verified: <i>Carole Ote</i>									
										Date: January 17, 2014		Description: XTL10Z1619/0117-X							
										Size: A		Scale: ---		Page: 1 of 1		Code Ident. No: 57104		Specification No.: F00729-X	
UNCONTROLLED DOCUMENT A later revision of this specification may exist.								 <p>A member of The Marmon Group of companies</p>		Wire & Cable Specification - HBR.04.86.D									