

**1. CONDUCTOR:**

- 1.1 Size and Material: 16 26/30 AWG tin-plated copper wire.
- 1.2 O.D.: .057" nom.

**2. INSULATION:**

- 2.1 Extruded special ETFE (Tefzel® 750).
- 2.2 Marking on the insulation: as per UL and CSA Standards.
- 2.3 O.D.: .077" nom.
- 2.4 Color: as per order (replace X in the part number and the description by 0-9 color code).

**3. PERFORMANCE:**

- 3.1 Voltage rating: 600 VAC R.M.S.
- 3.2 Temperature rating: 150°C

**4. REFERENCES:**

- 4.1 UL Subject 758 (AWM), Style 10086.
- 4.2 CSA Standard C22.2 No.210 (AWM), Class I Group A/B.




**5. NOTES:**

- 5.1 The usage temperature for Tefzel is -65°C.
- 5.2 The embrittlement point is -104°C.

**CUSTOMER APPROVAL**

Sign: \_\_\_\_\_

Date: \_\_\_\_\_

Engineering Change Notice No.	 <p style="font-size: small;">This specification is the property of Harbour Industries Canada Limited and may not be used or copied without the express written permission of Harbour Industries Canada Limited.</p>	Done: <i>Pierre Girard</i>	 <p style="font-size: x-small;">1365, boul. Industriel, Farnham, Quebec, Canada, J2N 2X3 Phone: (450) 293-5304 Fax: (450) 293-2421 Web site: www.harbourtd.com</p>			
		Date: February 2, 2009				Verified: <i>David L...</i>
			Date: February 2, 2009	Description: <b>XTL10Z1626/30-X</b>		
			Size: <b>A</b> Scale: ---    Page: 1 of 1	Code Ident. No: <b>57104</b>	Specification No.: <b>F04518-X</b>	Rev.: <b>---</b>
<b>UNCONTROLLED DOCUMENT</b> A later revision of this specification may exist.		 <p style="font-size: x-small;">A member of The Marmon Group of companies</p>				