

1. CONDUCTOR:

- 1.1 Size and Material: 18 AWG solid round tin-plated copper wire.
- 1.2 O.D.: .0403" nom.

2. INSULATION:

- 2.1 Extruded special ETFE (Terzel® 750).
- 2.2 Wall thickness: .012" nom.
- 2.3 Marking on insulation: as per UL and CSA Standards.
- 2.4 O.D.: .064" ± .002"
- 2.5 Color: as per order (replace X in the part number and the description by 0-9 color code).


3. PERFORMANCE:

- 3.1 Voltage rating: 600 VAC R.M.S.
- 3.2 Temperature rating: 200°C

4. REFERENCES:


- 4.1 UL Subject 758 (AWM), Style 10086.
- 4.2 CSA Standard C22.2 No. 210 (AWM), Class I, Group A/B.

CUSTOMER APPROVAL

Sign: 
 Date: 21 / MAY / 14

Engineering Change Notice No.	

This specification is the property of Harbour Industries Canada Limited and may not be used or copied without the express written permission of Harbour Industries Canada Limited.

Date: April 28, 2014
 Verified: 
 Date: April 28, 2014


 1335, boul. Industriel, Farnham, Québec Canada, J2N 2J3
 Phone: (450) 255-5304 Fax: (450) 255-2421 Web site: www.harbourind.com

Description: **XTL12218118-X**

UNCONTROLLED DOCUMENT
 A later revision of this specification may exist.

Size: **A** Scale: **---** Page: **1 Of 1**

Code Ident. No: **57104** Specification No.: **F00770-X** Rev: **---**