

1. CONDUCTOR:

- 1.1 Size and Material: 18 AWG, 7 strands, tin-plated copper wire.
- 1.2 O.D.: .0456" nom.

2. INSULATION:

- 2.1 Extruded special EFTE (Tefzel® 750).
- 2.2 Marking on the insulation: as per UL and CSA Standards.
- 2.3 O.D.: .0656" ± .0020"
- 2.4 Color: as per order (replace X in the part number and the description by 0-9 color code).

3. PERFORMANCE:

- 3.1 Voltage rating: 600 VAC R.M.S.
- 3.2 Temperature rating: 200°C
- 3.3 Flame rating: Horizontal flame (UL)/FT1 (CSA).
- 3.4 Insulation elongation: 200% min.
- 3.5 Elongation tensile strength: 2000 lbf/in² min.




4. REFERENCES:

- 4.1 UL Subject 758 (AWM), Style 10086.
- 4.2 CSA Standard C22.2 No.210 (AWM), Class I Group A/B.

CUSTOMER APPROVAL

Sign: _____

Date: _____

Engineering Change Notice No.							 <p>This specification is the property of Harbour Industries Canada Limited and may not be used or copied without the express written permission of Harbour Industries Canada Limited.</p>	Done: <i>Pierre Garand</i>		 <p>1365, boul. Industriel, Farnham, Quebec, Canada, J2N 2X3 Phone: (450) 293-5304 Fax: (450) 293-2421 Web site: www.harbourfd.com</p>					
1364								Date: August 26, 2008							
								Verified: <i>Carrie</i>							
								Date: August 27, 2008		Description: XTL10Z187/0152-X					
								Size: A Scale: --- Page: 1 of 1					Code Ident. No: 57104		Specification No.: F00080-X
UNCONTROLLED DOCUMENT A later revision of this specification may exist.							 <p>A member of The Marmon Group of companies</p>								