

# UL 10086 (continued)

Catalog Number	Size (AWG)	Stranding (No./AWG)	Insulation Thickness (mils)	Overall Diameter (inches)	Weight (lbs/1000 ft)	Part Number	
						U.S.	Canada
TZ10086-181T	18	1/18	10	.060	6	-	2421
TZ10086-187T	18	7/26	10	.069	6.5	-	2422
TZ10086-1819S	18	19/30	10	.067	7	-	2423
TZ10086-161T	16	1/16	10	.071	9	-	2424
TZ10086-167T	16	7/.0192"	10	.078	10	-	2425
TZ10086-1619S	16	19/.0117"	10	.076	10	-	2426
TZ10086-141T	14	1/14	10	.084	14	-	2427
TZ10086-147T	14	7/.0242"	10	.092	15	-	2428
TZ10086-1419S	14	19/.0147"	10	.089	16	-	2429
TZ10086-121T	12	1/12	15	.111	23	-	2430
TZ10086-1219T	12	19/.0185"	15	.119	23	-	2431
TZ10086-1237S	12	37/.0133"	15	.123	24	-	2432
TZ10086-1019T	10	19/.0234"	15	.143	37	-	2433
TZ10086-1037T	10	37/.0167"	15	.145	34	-	2434
TZ10086-10105S	10	105/30	15	.154	36	-	2435
TZ10086-819T	8	19/.0295"	30	.201	63	-	2436
TZ10086-8133S	8	133/29	30	.220	65	-	2437
TZ10086-619T	6	19/.0372	30	.241	96	-	2438
TZ10086-6133S	6	133/27	30	.262	99	-	2439
TZ10086-4133T	4	133/25	30	.325	150	-	2440
TZ10086-2133T	2	133/23	30	.395	231	-	2441
TZ10086-1259T	1	259/25	45	.462	304	-	2442
TZ10086-01259T	1/0	259/24	45	.514	375	-	2443
TZ10086-02259T	2/0	259/23	45	.567	466	-	2444
TZ10086-03259T	3/0	259/22	45	.620	579	-	2445
TZ10086-04259T	4/0	259/21	45	.676	722	-	2446

<sup>1</sup>Suffix "S" on Catalog Number denotes silver plated copper; suffix "T", tin plated copper.

*All figures referenced are nominal.*



**Harbour**  
INDUSTRIES