

**1. CONDUCTOR:**

- 1.1 Size and Material: 24 7/32 AWG tin-plated copper wire.
- 1.2 O.D.: .024" nom.

**2. INSULATION:**

- 2.1 Extruded special EFTE (Tefzel® 750).
- 2.2 Marking on the insulation: not required as per UL and CSA Standards.
- 2.3 O.D.: .044" nom.
- 2.4 Color: as per order (replace X in the part number and the description by 0-9 color code).

**3. PERFORMANCE:**

- 3.1 Voltage rating: 600 VAC R.M.S.
- 3.2 Temperature rating: 150°C


**4. REFERENCES:**

- 4.1 UL Subject 758 (AWM), Style 10086.
- 4.2 CSA Standard C22.2 No.210 (AWM), Class I Group A/B.

**CUSTOMER APPROVAL**

Sign: \_\_\_\_\_

Date: \_\_\_\_\_

Engineering Change Notice No.							This specification is the property of Harbour Industries Canada Limited and may not be used or copied without the express written permission of Harbour Industries Canada Limited.	Done: <i>Pierre Garand</i>	 1365, boul. Industriel, Farnham, Quebec, Canada, J2N 2X3 Phone: (450) 293-5304 Fax: (450) 293-2421 Web site: www.harbourind.com			
						Date: May 16, 2014						
						Verified: <i>Carrie Lott</i>		Description: <b>XTL10Z247/32-X</b>				
						Date: May 16, 2014						
<b>UNCONTROLLED DOCUMENT</b> A later revision of this specification may exist.								Size: <b>A</b>	Scale: ---	Page: 1 of 1	Code Ident. No: <b>57104</b>	Specification No.: <b>F00546-X</b>