

1. CONDUCTOR:

- 1.1 Size and Material: 20 19/32 AWG tin-plated copper wire.
- 1.2 O.D.: .0385" nom.

2. INSULATION:

- 2.1 Extruded special ETFE (Tefzel® 750).
- 2.2 Marking on the insulation: Not required.
- 2.3 O.D.: .0505" nom.
- 2.4 Color: As per order (replace X in the part number and the description by 0-9 color code).

3. PERFORMANCE:

- 3.1 Voltage rating: 300 VAC R.M.S.
- 3.2 Temperature rating: 150°C


4. REFERENCES:

- 4.1 UL Subject 758 (AWM), Style 10109.
- 4.2 CSA Standard C22.2 No.210 (AWM), Class I Group A/B.

CUSTOMER APPROVAL

Sign: _____

Date: _____

Engineering Change Notice No.								This specification is the property of Harbour Industries Canada Limited and may not be used or copied without the express written permission of Harbour Industries Canada Limited.		Done: <i>Daniel Curson</i>		 1365, boul. Industriel, Farnham, Quebec, Canada, J2N 2X3 Phone: (450) 293-5304 Fax: (450) 293-2421 Web site: www.harbourind.com						
										Date: June 6, 2016								
										Verified: <i>David Lott</i>								
										Date: June 6, 2016		Description: XTL6Z2019/32						
										Size: A	Scale: ---	Page: 1 of 1	Code Ident. No: 57104	Specification No.: Q04140-X	Rev. ---			
UNCONTROLLED DOCUMENT A later revision of this specification may exist.																		